

Lifting Beam T-A-VR

Product information



The lifting beam of the T-A-VR series has an eye suspension for single hooks according to DIN 15401 on the crane side and adjustable lifting frames on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry.

Material: Construction steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +100°C

Finish: RAL 3000 (flame red)

Standard: EN 13155

Part Code	WLL ton	Length m	H mm	L min. mm	L max. mm	S mm	T mm	W mm	Weight kg	Delivery time
6205TAVR22000	2	1-2	135	1,000	2,000	50	20	65	53	7
6205TAVR23000	2	1.5-3	135	1,400	3,000	50	20	65	100	7
6205TAVR24000	2	2-4	135	2,000	4,000	50	20	65	127	7
6205TAVR25000	2	2.5-5	135	2,500	5,000	50	20	65	197	7
6205TAVR26000	2	3-6	135	3,000	6,000	50	20	65	229	7
6205TAVR32000	3	1-2	150	1,000	2,000	100	25	75	76	7
6205TAVR33000	3	1.5-3	150	1,500	3,000	100	25	75	131	7
6205TAVR34000	3	2-4	150	2,000	4,000	100	25	75	165	7

6205TAVR35000	3	2.5-5	150	2,500	5,000	100	25	75	246	7
6205TAVR36000	3	3-6	150	3,000	6,000	100	25	75	297	7
6205TAVR52000	5	1-2	170	1,000	2,000	100	25	85	105	7
6205TAVR53000	5	1.5-3	170	1,500	3,000	100	25	85	167	7
6205TAVR54000	5	2-4	170	2,000	4,000	100	25	85	249	7
6205TAVR55000	5	2.5-5	170	2,500	5,000	100	25	85	363	7
6205TAVR56000	5	3-6	170	3,000	6,000	100	25	85	426	7
6205TAVR82000	8	1-2	210	1,000	2,000	100	30	105	151	7
6205TAVR83000	8	1.5-3	210	1,500	3,000	100	30	105	222	7
6205TAVR84000	8	2-4	210	2,000	4,000	100	30	105	326	7
6205TAVR85000	8	2.5-5	210	2,500	5,000	100	30	105	424	7
6205TAVR86000	8	3-6	210	3,000	6,000	100	30	105	642	7
6205TAVR102000	10	1-2	240	1,000	2,000	100	40	120	157	7
6205TAVR103000	10	1.5-3	240	1,500	3,000	100	40	120	252	7
6205TAVR104000	10	2-4	240	2,000	4,000	100	40	120	349	7
6205TAVR105000	10	2.5-5	240	2,500	5,000	100	40	120	524	7
6205TAVR106000	10	3-6	240	3,000	6,000	100	40	120	670	7

Blueprint

