



## Clevis Foundry Hook X-046 Grade 10

### Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Designed for the assembly of chain slings where wide throat openings are necessary.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1

**Warning:** Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

**Safety factor:** 4:1

**Grade:** 10

Part Code	WLL ton	EWL	For chain Grade 10 Ø mm	A mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
402300250770	2.5	133	7,8	9	27	133	62	19	0.95	3
402300400770	4	163	10	11	32	163	74	23	1.8	3
402300670770	6.7	200	13	14	39	200	88	32	3.6	3

## Blueprint

