



## HOISTMAN hand chain hoist

### Product information



The Rema® HOISTMAN is a lightweight mini-hand chain hoist. Very compact for use in confined spaces and where a low self weight is desirable.

#### Properties

- Steel chromed body.
- Little operating effort at maximum load due to bearing shafts.
- Double pawl system.
- Self-locking brake that holds the load at any desired height.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 10).
- Galvanized hand chain

#### Standard delivery

- 2,5 meters lifting height (maximum distance between top and bottom hook).
- 2 meters operating height.

**Marking:** According to standard, CE-marked

**Standard:** EN 13157, EN 818-7

| Part Code             | GTIN No. | WLL ton | Lifting height m | Number of falls | Model     | Load Chain dia x pitch mm | Hand Chain Ø x pitch mm | Chain falls | Construction height mm | Hand force max. kg | A   | B  | C  | D   | E  | F  | G  | H | I   | Weight kg | Delivery time |
|-----------------------|----------|---------|------------------|-----------------|-----------|---------------------------|-------------------------|-------------|------------------------|--------------------|-----|----|----|-----|----|----|----|---|-----|-----------|---------------|
| R01000008717365000676 | 0.15     | 2.5     | 1                | HOISTMAN-150KG  | 3.1 X 9.3 | 2.5 X 14                  | 1                       | 220         | 17                     | 220                | 103 | 46 | 57 | 102 | 14 | 24 | 11 | 9 | 2.8 | 2         |               |
| R01000028717365115196 | 0.25     | 2.5     | 1                | HOISTMAN-250KG  | 3.1 X 9.3 | 2.5 X 14                  | 1                       | 220         | 20                     | 220                | 103 | 46 | 57 | 102 | 14 | 24 | 11 | 9 | 2.8 | 2         |               |

## Blueprint

