



H-100 hand chain hoist

Product information



Model Rema® H-100 is a robust hand chain hoist designed for heavy and increased loads, bearing safety, ergonomics and low operating effort in mind.

Properties

- Low operating effort at full load due to bearing shafts.
- Double brake pawl system.
- Self-locking brake that can hold loads at any desired height.
- Suspension and load hooks equipped with safety latches.
- The load hook will yield under overload instead of breaking.
- Zinc-plated load chain (grade 8 in compliance with EN 818-7).
- Zinc plated hand chain.
- Reliable steel plate housing in orange finish.

Standard delivery

- 3 m hoisting height.
- 2,5 m operating height.

Option

- Available in any other hoisting and operational heights.

Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

Part Code	GTIN No.	WLL ton	Lifting height m	Model	Load Chain dia x pitch mm	Hand Chain Ø x pitch mm	Chain falls	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	Weight kg	Delivery time
R0100001-38717365264191		0.5	3	H100-500KG-3m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	10	2

R0100001-48717365264207	0.5	4	H100-500KG-4m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	11.6	2
R0100001-58717365264214	0.5	5	H100-500KG-5m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	13.2	2
R0100001-68717365264221	0.5	6	H100-500KG-6m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	14.8	2
R0100001-78717365090370	0.5	7	H100-500KG-7m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	16.4	2
R0100001-88717365090387	0.5	8	H100-500KG-8m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	18	2
R0100001-98717365089930	0.5	9	H100-500KG-9m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	19.6	2
R0100001-108717365089947	0.5	10	H100-500KG-10m	5.0 x 15	5.0 x 23.6	1	277	22	277	155	65	90	140	26	36	17	13	21.2	2
R0100003-38717365264238	1	3	H100-1000KG-3m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	13	2
R0100003-48717365264245	1	4	H100-1000KG-4m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	15	2
R0100003-58717365264252	1	5	H100-1000KG-5m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	17	2
R0100003-68717365264269	1	6	H100-1000KG-6m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	19	2
R0100003-78717365089954	1	7	H100-1000KG-7m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	21	2
R0100003-88717365089961	1	8	H100-1000KG-8m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	23	2
R0100003-98717365089978	1	9	H100-1000KG-9m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	25	2
R0100003-108717365089985	1	10	H100-1000KG-10m	6.3 x 19.1	5.0 x 23.6	1	303	26	303	160	69	91	160	30	43	22	13	27	2
R0100005-38717365264276	1.6	3	H100-1600KG-3m	7.1 x 21.0	5.0 x 23.6	1	338	34	338	167.5	75	92.5	183	35	48	27	20	16	2
R0100005-68717365264306	1.6	6	H100-1600KG-6m	7.1 x 21.0	5.0 x 23.6	1	338	34	338	167.5	75	92.5	183	35	48	27	20	22.6	2
R0100007-38717365264313	2	3	H100-2000KG-3m	8.0 x 24.2	5.0 x 23.6	1	379	34	379	183	83	100	215	38	53	29	22	22	2
R0100007-68717365264344	2	6	H100-2000KG-6m	8.0 x 24.2	5.0 x 23.6	1	379	34	379	183	83	100	215	38	53	29	22	29.2	2
R0100009-38717365264351	3.1	3	H100-3100KG-3m	7.1 x 21.0	5.0 x 23.6	2	516	36	516	167.7	75	92.5	230	44	60	37	27	25	2
R0100009-68717365264382	3.1	6	H100-3100KG-6m	7.1 x 21.0	5.0 x 23.6	2	516	36	516	167.7	75	92.5	230	44	60	37	27	35.2	2
R0100011-38717365264399	5	3	H100-5000KG-3m	9.0 x 27.2	5.0 x 23.6	2	613	36	613	190	90	100	282	53	70	46	34	41	2

R0100011-68717365264429	5	6	H100-5000KG-6m	9.0 x 27.2	5.0 x 23.6	2	613	36	613	190	90	100	282	53	70	46	34	54.5	2
-------------------------	---	---	----------------	------------	------------	---	-----	----	-----	-----	----	-----	-----	----	----	----	----	------	---

Blueprint

