



Select 200 Hand chain hoist (high capacities)

Product information



The Rema® Select 200 is a robust manual chain hoist for heavy and intensive use where safety, ergonomics and a low operating effort are paramount.

Properties

- Equipped with a double pawl system.
- Brake is provided with asbestos free friction discs.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain Grade 8.
- Galvanized hand chain.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.
- Excluding overload protection.

Option

- Available in any other lifting and operational heights.



Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

Part Code	GTIN No.	WLL	Lifting height	Model	Load Chain dia x pitch	Hand Chain Ø x pitch	Chain falls	Construction height	Hand force max.	A	B	C	D	H	Weight	Delivery time
		ton	m		mm	mm		mm	kg	mm	mm	mm	mm	mm	kg	
R0120017-4	8717365174759	15	4	S200/15.000KG/4M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	127	2
R0120017-5	8717365174766	15	5	S200/15.000KG/5M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	140	2
R0120017-3	8717365174742	15	3	S200/15.000KG/3M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	162.6	2
R0120017-6	8717365174773	15	6	S200/15.000KG/6M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	162.6	2
R0120017-7	8717365174780	15	7	S200/15.000KG/7M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	163	2
R0120017-8	8717365174797	15	8	S200/15.000KG/8M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	175	2
R0120017-9	8717365174803	15	9	S200/15.000KG/9M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	187	2
R0120017-10	8717365174810	15	10	S200/15.000KG/10M	9.0 x 27	5.0 x 23.7	6	920	40	386	183	62	77	920	199	2
R0120019-4	8717365174834	20	4	S200/20.000KG/4M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	164	2
R0120019-5	8717365174841	20	5	S200/20.000KG/5M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	180	2
R0120019-3	8717365174827	20	3	S200/20.000KG/3M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	186	2
R0120019-6	8717365174858	20	6	S200/20.000KG/6M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	186	2
R0120019-7	8717365174865	20	7	S200/20.000KG/7M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	212	2
R0120019-8	8717365174872	20	8	S200/20.000KG/8M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	229	2
R0120019-9	8717365174889	20	9	S200/20.000KG/9M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	245	2
R0120019-10	8717365174896	20	10	S200/20.000KG/10M	9.0 x 27	5.0 x 23.7 (2x)	8	1,060	40	577	183	75	90	1,060	262	2
R0120021-3	8717365177880	30	3	S200/30000KG/3M	10.0 x 28	5.0 x 23.7 (2x)	12	980	40	705	452	85	110	1,450	200	2

Blueprint

