



X-Line block chain hoist

Product information



The Rema® X-Line hand hoist is the solution for all demanding lifting tasks. With low operating force and increased safety system, you work efficiently and safely. The asbestos-free friction discs and wear-resistant load chain make use even more comfortable. The gradual bulging under overload and the orange powder coating provide additional safety and visibility. Available from 3 meters lifting height and 2.5 meters operating height, the Rema® X-Line hand hoist is suitable for any demanding task.

Properties

- Low operating force at full load.
- Increased operational safety due to double pawl system.
- Brake is provided with asbestos free friction discs.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).
- Galvanized hand chain.
- Steel housing with orange colored powder coating.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.

Option

- Available in any other hoisting and operational heights.

Norm:

- EN12100-1/2, EN13157, EN818-7



Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

Part Code	GTIN No.	WLL	Lifting height	Model	Load Chain dia x pitch	Hand Chain Ø x pitch	Chain falls	Construction height	Hand force max.	A	B	C	D	H	Weight	Delivery time
		ton	m		mm	mm		mm	kg	mm	mm	mm	mm	mm	kg	
R0170000-3	8717365112539	0.25	3	X-CH/250KG/3M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	6	2
R0170000-4	8717365112423	0.25	4	X-CH/250KG/4M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	7.4	2
R0170000-5	8717365112430	0.25	5	X-CH/250KG/5M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	8.8	2
R0170000-6	8717365112553	0.25	6	X-CH/250KG/6M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	10.2	2
R0170000-7	8717365112447	0.25	7	X-CH/250KG/7M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	11.6	2
R0170000-8	8717365112454	0.25	8	X-CH/250KG/8M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	13	2
R0170000-9	8717365112461	0.25	9	X-CH/250KG/9M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	14.4	2
R0170000-10	8717365112478	0.25	10	X-CH/250KG/10M	4.0 x 12	5.0 x 23.7	1	260	23.5	108	106	20	30	260	15.8	2
R0170001-3	8717365096211	0.5	3	X-CH/500KG/3M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	10	2
R0170001-4	8717365096440	0.5	4	X-CH/500KG/4M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	11.6	2
R0170001-5	8717365096457	0.5	5	X-CH/500KG/5M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	13.2	2
R0170001-6	8717365096228	0.5	6	X-CH/500KG/6M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	14.8	2
R0170001-7	8717365096464	0.5	7	X-CH/500KG/7M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	16.4	2
R0170001-8	8717365096471	0.5	8	X-CH/500KG/8M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	18	2
R0170001-9	8717365096488	0.5	9	X-CH/500KG/9M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	19.6	2
R0170001-10	8717365096495	0.5	10	X-CH/500KG/10M	5.0 x 15	5.0 x 23.7	1	280	24.9	130	128	22	34	280	21.2	2
R0170003-3	8717365096235	1	3	X-CH/1000KG/3M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	12	2

R0170003-4	8717365096501	1	4	X-CH/1000KG/4M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	13.9	2
R0170003-5	8717365096518	1	5	X-CH/1000KG/5M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	15.8	2
R0170003-6	8717365096242	1	6	X-CH/1000KG/6M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	17.7	2
R0170003-7	8717365096525	1	7	X-CH/1000KG/7M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	19.6	2
R0170003-8	8717365096532	1	8	X-CH/1000KG/8M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	21.5	2
R0170003-9	8717365096549	1	9	X-CH/1000KG/9M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	23.4	2
R0170003-10	8717365096556	1	10	X-CH/1000KG/10M	6.3 x 19	5.0 x 23.7	1	330	28.4	150	142	26	39	330	25.3	2
R0170005-3	8717365096259	1.5	3	X-CH/1500KG/3M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	16	2
R0170005-4	8717365096563	1.5	4	X-CH/1500KG/4M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	18.2	2
R0170005-5	8717365096570	1.5	5	X-CH/1500KG/5M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	20.4	2
R0170005-6	8717365096266	1.5	6	X-CH/1500KG/6M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	22.6	2
R0170005-7	8717365096587	1.5	7	X-CH/1500KG/7M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	24.8	2
R0170005-8	8717365096594	1.5	8	X-CH/1500KG/8M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	27	2
R0170005-9	8717365096600	1.5	9	X-CH/1500KG/9M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	29.2	2
R0170005-10	8717365096617	1.5	10	X-CH/1500KG/10M	7.1 x 21	5.0 x 23.7	1	360	30.8	170	158	29	42	360	31.4	2
R0170007-3	8717365096273	2	3	X-CH/2000KG/3M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	20	2
R0170007-4	8717365096624	2	4	X-CH/2000KG/4M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	22.4	2
R0170007-5	8717365096631	2	5	X-CH/2000KG/5M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	24.8	2
R0170007-6	8717365096280	2	6	X-CH/2000KG/6M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	27.2	2
R0170007-7	8717365096648	2	7	X-CH/2000KG/7M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	29.6	2
R0170007-8	8717365096655	2	8	X-CH/2000KG/8M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	32	2
R0170007-9	8717365096662	2	9	X-CH/2000KG/9M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	34.4	2
R0170007-10	8717365096679	2	10	X-CH/2000KG/10M	8.0 x 24	5.0 x 23.7	1	385	34.3	185	175	35	49	385	36.8	2

R0170009-3	8717365096297	3	3	X-CH/3000KG/3M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	26	2
R0170009-4	8717365096686	3	4	X-CH/3000KG/4M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	29.4	2
R0170009-5	8717365096693	3	5	X-CH/3000KG/5M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	32.8	2
R0170009-6	8717365096303	3	6	X-CH/3000KG/6M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	36.2	2
R0170009-7	8717365096709	3	7	X-CH/3000KG/7M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	39.6	2
R0170009-8	8717365096716	3	8	X-CH/3000KG/8M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	43	2
R0170009-9	8717365096723	3	9	X-CH/3000KG/9M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	46.4	2
R0170009-10	8717365096730	3	10	X-CH/3000KG/10M	7.1 x 21	5.0 x 23.7	2	510	34.3	220	158	37	50	510	49.8	2
R0170011-3	8717365096310	5	3	X-CH/5000KG/3M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	41.5	2
R0170011-4	8717365096747	5	4	X-CH/5000KG/4M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	46	2
R0170011-5	8717365096754	5	5	X-CH/5000KG/5M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	50.5	2
R0170011-6	8717365096327	5	6	X-CH/5000KG/6M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	55	2
R0170011-7	8717365096761	5	7	X-CH/5000KG/7M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	59.5	2
R0170011-8	8717365096778	5	8	X-CH/5000KG/8M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	64	2
R0170011-9	8717365096785	5	9	X-CH/5000KG/9M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	68.5	2
R0170011-10	8717365096792	5	10	X-CH/5000KG/10M	9.0 x 27	5.0 x 23.7	2	615	37.2	255	183	43	60	615	73	2
R0170015-3	8717365096433	10	3	X-CH/10000KG/3M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	75	2
R0170015-4	8717365096808	10	4	X-CH/10000KG/4M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	83	2
R0170015-5	8717365096815	10	5	X-CH/10000KG/5M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	91	2
R0170015-6	8717365096426	10	6	X-CH/10000KG/6M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	99	2
R0170015-7	8717365096822	10	7	X-CH/10000KG/7M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	107	2
R0170015-8	8717365096839	10	8	X-CH/10000KG/8M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	115	2
R0170015-9	8717365096846	10	9	X-CH/10000KG/9M	9.0 x 27	5.0 x 23.7	4	820	40	360	183	47	65	820	123	2

R0170015-10 8717365096853	10	10	X-CH/10000KG/10M	9.0 x 27	5.0 x 23.7	4	820	40	360 183 47 65 820 131	2
---------------------------	----	----	------------------	----------	------------	---	-----	----	-----------------------	---

Blueprint

