



EOB eye-bolt (Grade 8)

Product information



High-alloyed steel eyebolt. Eye bolts may only be tightened by hand.
Safe workload, under a maximum angle of 60° as shown.
The lifting eye must not be loaded sideways.

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4

Grade: 8

Part Code	GTIN No.	WLL	Thread mm	Model	A mm	B mm	C mm	D mm	M mm	Weight	Delivery time
R2675108	8717365097157	0.4	M8	EOB08	34	7	20	24	M8 x 1,25	0.05	2
R2675110	8717365097164	0.7	M10	EOB10	38	8	22	30	M10 x 1,50	0.08	2
R2675112	8717365097171	1	M12	EOB12	47	10	26	36	M12 x 1.75	0.14	2
R2675114	8717365097188	1.2	M14	EOB14	57	14	29	40	M14 x 2.00	0.25	2
R2675116	8717365097195	1.5	M16	EOB16	65	14	35	55	M16 x 2.00	0.36	2
R2675118	8717365097201	2	M18	EOB18	65	14	35	54	M18 x 2.5	0.38	2
R2675120	8717365097218	2.5	M20	EOB20	73	16	39	59	M20 x 2.50	0.55	2
R2675124	8717365097225	4	M24	EOB24	95	20	54	84	M24 x 3.00	1.12	2
R2675127	8717365097232	5	M27	EOB27	95	20	54	84	M27 x 3.00	1.18	2
R2675130	8717365097249	6	M20	EOB30	108	24	59	100	M30 x 3.50	1.84	2
R2675136	8717365097256	8	M36	EOB36	118	25	67	118	M36 x 4.00	2.44	2
R2675142	8717365097263	10	M42	EOB42	139	31	79	135	M42 x 4.50	3.97	2