



## Eye-bolt (DIN-580)

### Product information



High-alloyed steel eyebolt. Eye bolts may only be tightened by hand.  
Safe workload, under a maximum angle of 60° as shown.  
The lifting eye must not be loaded sideways.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1, DIN 580

**Safety factor:** 4

**Grade:** 8

| Part Code | GTIN No.      | WLL ton | Thread mm | Model         | A mm | B mm | C mm | D mm | M mm       | Weight kg | Delivery time |
|-----------|---------------|---------|-----------|---------------|------|------|------|------|------------|-----------|---------------|
| R2675308  | 8717365115202 | 0.4     | M8        | DIN580-G8-M8  | 34   | 7    | 20   | 13   | M8 x 1,25  | 0.05      | 2             |
| R2675310  | 8717365115219 | 0.7     | M10       | DIN580-G8-M10 | 38   | 8    | 22   | 17   | M10 x 1,50 | 0.07      | 2             |
| R2675312  | 8717365115226 | 1       | M12       | DIN580-G8-M12 | 47   | 10   | 26   | 21   | M12 x 1.75 | 0.13      | 2             |
| R2675316  | 8717365115233 | 1.5     | M16       | DIN580-G8-M16 | 64   | 14   | 35   | 27   | M16 x 2.00 | 0.34      | 2             |
| R2675320  | 8717365115240 | 2.5     | M20       | DIN580-G8-M20 | 73   | 16   | 39   | 30   | M20 x 2.50 | 0.52      | 2             |
| R2675324  | 8717365115257 | 4       | M24       | DIN580-G8-M24 | 95   | 20   | 54   | 36   | M24 x 3.00 | 0.99      | 2             |