



Eye hook type 14A (Grade 8)

Product information



Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 1677-2

Note: Safety latch.

Warning: Cannot be rotated under load

Part Code	GTIN No.	WLL ton	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg	Delivery time
R3009001	8717365013256	1.25	S6703A-1.25T	52	28	31	75	20	148	118	11	0.49	2
R3009003	8717365013263	1.6	S6703A-1.6T	67	35	40	81	22	180	145	14	0.95	2
R3009005	8717365013270	2.5	S6703A-2.5T	81	43	47	92	27	208	167	17	1.48	2
R3009007	8717365013287	3.2	S6703A-3.2T	81	47	47	103	30	222	180	17	1.79	2
R3009009	8717365013294	5.4	S6703A-5.4T	106	64	64	125	37	274	217	21	3.8	2
R3009011	8717365013300	8	S6703A-8T	129	69	78	165	49	337	276	26	7.4	2
R3009013	8717365013317	11.5	S6703A-11.5T	148	68	82	193	53	395	310	22	14.9	2
R3009015	8717365013324	16	S6703A-16T	165	84	92	221	58	445	352	24	15	2
R3009016	8717365261190	22	S6703A-22T	200	107	115	282	87	543	434	29	27	2

Blueprint

