



## RGL gear winches

### Product information



#### Properties

- Construction according to DIN 152.
- Braked design with double pawl system.
- Crank gradually adjustable in length.
- Drum and shafts provided with bearings.
- Freewheel, through protected pawl system.
- Powdercoating RAL 2004.

#### Standard delivery

- Does not include wire rope.

#### Option

- Steel wire rope on request with hook and safety latch.

**Marking:** According to standard, CE-marked

**Standard:** EN 12100, EN 13157

| Part Code | GTIN No.      | WLL ton | Model   | Cable Diameter mm | Gear ratio | Max. reel capacity mm | Length handle mm | Load capacity last layer kg | load capacity 1st layer kg | Weight kg | Delivery time |
|-----------|---------------|---------|---------|-------------------|------------|-----------------------|------------------|-----------------------------|----------------------------|-----------|---------------|
| R2017001  | 8717365259265 | 0.15    | RGL-150 | 4                 | 2.84 :1    | 22                    | 250/100          | 45                          | 150                        | 9.2       | 2             |
| R2017003  | 8717365259272 | 0.3     | RGL-300 | 5                 | 6.67:1     | 30                    | 250/100          | 100                         | 300                        | 16.5      | 2             |
| R2017005  | 8717365259289 | 0.5     | RGL-500 | 6                 | 7.75 :1    | 30                    | 250/100          | 300                         | 500                        | 18.5      | 2             |

Technical data

| Model   | A   | B   | C   | D   | F   | G  | H  | J  | K  | L  | M  | N  | P  | Q  | R  | S  | T  | U  | V  |
|---------|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
|         | mm  | mm  | mm  | mm  | mm  | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| RGL-150 | 180 | 324 | 150 | 150 | 154 |    |    |    |    |    |    |    |    |    |    |    |    |    |    |

Blueprint

