

Closed Body Rigging Screws G-6340

Product information



For tensioning of ropes, cables and the like. With eye in both ends.

Material: Mild steel.

Marking: CE-marked

Finish: Hot dipped galvanized.

Note: End fittings of 6 and 8 mm rigging screws are electro-galvanized.

Safety factor: 5:1

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	Weight kg	Delivery time
422100020320	0.2	6	100	160	240	5.5	11	11	6	0.13	7
422100030320	0.32	8	108	175	255	6	12	12	8	0.2	7
422100050320	0.5	10	125	205	300	8.5	13	13	8	0.6	7
422100070320	0.7	12	195	320	480	11	30	15	10	0.8	7
422100120320	1.2	16	230	380	555	12	40	20	11	1.4	7
422100150320	1.5	20	270	455	660	16	50	24	12	2.4	7
422100220320	2.2	22	295	495	720	16	50	24	12	3	7
422100320320	3.2	24	325	540	790	19	56	28	12	4	7
422100480320	4.8	33	370	660	940	29	70	35	14	9	7
422100600320	6	39	400	720	1.02	35	80	40	15	11.5	7
422100850320	8.5	45	400	721	879	31	49	49	16	20.8	7

Blueprint

