

Fast Connector Socket FCS Spin Resistant - with bolt



Product information

Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Can be used to terminate all constructions of wire rope including high performance ropes, anti-rotation ropes and standard 6 strand ropes.
The connector has to be moulded / casted on the steel wire rope with wirelock resin.

Features: Designed for use with mobile cranes.

Material: Quenched and tempered cast steel.

Finish: Blue painted (P) or hot dip galvanized (G).

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Part Code	Code	Rope Ø range mm	MBL	Finish	TB mm	TL mm	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	Weight kg	Delivery time
122102600282	FCS 705 B.SR.G	23-26	75	Galvanized	138	298	115	123	60	28	51	22	51	104	60	95	90	11	30
122102900282	FCS 706 B.SR.G	27-29	90	Galvanized	160	357	140	152	65	32	57	25	57	114	70	107	116	16	30
122103200282	FCS 707 B.SR.G	30-32	125	Galvanized	165	382	150	159	73	36	63	28	63	126	80	119	120	18	30
122103600282	FCS 708 B.SR.G	33-36	125	Galvanized	185	404	160	171	73	39	69	28	69	126	85	125	130	23	30
122103900282	FCS 709 B.SR.G	37-39	150	Galvanized	201	443	176	187	80	42	76	30	76	142	90	136	142	29	30
122104200282	FCS 710 B.SR.G	40-42	170	Galvanized	209	474	188	198	88	45	76	33	76	156	95	142	150	36	30
122104800282	FCS 711 B.SR.G	43-48	225	Galvanized	237	542	210	232	100	52	89	39	89	176	110	167	175	58	30

Blueprint

