



Closed Body Rigging Screws G-6343

Product information

Closed body rigging screws / turnbuckles G-6343 are fitted with a Jaw with safety bolt on both ends. Lock nuts are included.

Material: Mild steel.

Marking: CE-marked

Finish: Hot dipped galvanized.

Note: The Jaws of the rigging screws up to 8 mm are electro-galvanized.

Safety factor: 5:1

Part Code	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg	Delivery time
422100020280	0.2	6	100	170	250	5	16	7	20	13	0.16	7
422100030280	0.32	8	108	199	279	6	22	9	24	14	0.27	7
422100050280	0.5	10	125	222	312	8	22	10.5	28	19	0.45	7
422100070280	0.7	12	195	315	470	10	27	13	34	23	0.85	7
422100120280	1.2	16	230	388	568	12	33	18	42	29	1.57	7
422100150280	1.5	20	270	449	654	16	38	20	51	33	2.67	7
422100220280	2.2	22	295	490	715	20	45	25	55	38	3.68	7
422100320280	3.2	24	325	538	793	22	52	30	70	46	5.3	7
422100480280	4.8	33	370	680	965	30	70	38	82	60	12	7
422100600280	6	39	400	707	1,002	33	70	45	85	76	14.2	7
422100850280	8.5	45	400	761	1,011	39	86	50	94	85	20.8	7
422101100280	11	48	400	780	1,005	45	97	58	98	92	24	7

Blueprint

