



Open Body Turnbuckles Jaw - Jaw

Product information

General:

- Generally to ASTM F 1145-92
- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals or over 5x WLL

Part Code	WLL ton	Thread dia. X Take-up mm	L min. mm	L max. mm	A mm	P mm	U mm	W mm	Weight kg	Delivery time
422100230200	0.23	6.35 x 102	175	277	121	6	15	11	0.16	7
422100360200	0.36	7.94 x 114	212	314	138	6	22	13	0.24	7
422100540200	0.54	9.53 x 152	258	410	181	8	22	14	0.37	7
422100100200	1	12.7 x 152	292	470	190	10	27	16	0.71	2
422100100205	1	12.7 x 229	368	622	266	10	27	16	0.79	7
422100100206	1	12.7 x 305	445	775	343	10	27	15	1.09	2
422100160200	1.59	15.9 X 152	325	509	200	13	33	20	1.23	7
422100160205	1.59	15.9 X 229	401	662	276	13	33	20	1.56	7

422100160206	1.59	15.9 x 305	478	814	353	13	33	20	1.77	7
422100240200	2.36	19.1 X 152	356	546	210	16	38	24	1.86	7
422100240205	2.36	19.1 x 229	432	699	286	16	38	24	2.48	7
422100240206	2.36	19.1 X 305	508	851	362	6	38	24	2.98	2
422100240207	2.36	19.1 x 457	660	1,156	514	16	38	24	3.64	7
422100330200	3.27	22.2 x 305	543	892	370	19	44	29	3.71	7
422100330205	3.27	22.2 x 457	695	1,197	523	19	44	29	4.89	7
422100450205	4.54	25.4 X 152	425	628	228	22	52	34	4.62	7
422100450207	4.54	25.4 x 305	577	933	380	22	52	34	5.53	7
422100450206	4.54	25.4 x 457	729	1,237	532	22	52	34	6.87	7
422100450200	4.54	25.4 x 610	882	1,542	685	22	52	34	8.2	7
422100690200	6.89	31.8 X 305	644	1,012	384	28	71	44	9.34	7
422100690205	6.89	31.8 x 45	796	1,317	537	28	71	44	11.2	7
422100690206	6.89	31.8 610	948	1,622	689	28	71	44	12.8	7
422100970200	9.71	38.1 x 305	673	1,073	400	35	71	52	13.9	7
422100970205	9.71	8.1 x 457	826	1,359	553	35	71	52	16.7	7
422100970206	9.71	38.1 x 610	978	1,664	705	35	71	52	18.9	7
422101270200	12.7	44.5 X 457	899	1,356	8	41	86	66	24.5	7
422101270205	12.7	44.5 X 610	51	1,661	721	41	86	66	28.7	7
422101680200	16.8	51.0 x 610	1,157	1,766	38	51	94	66	46.5	7
422102720200	27.2	63.5 x 610	1,244	1,854	9	57	113	76	75	7
422103400200	34	70.0 x 610	1,289	1,899	-	70	106	92	90	7

Blueprint

