



## Super Reeve Connector Socket SCS Spin resistant - with bolt

### Product information

**General:** A revolutionary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available in the market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system. This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques. The standard finish of our sockets is blue. Hot dipped galvanized is also available.

**Material:** Quenched and tempered cast steel.

| Part Code    | Code             | Rope Ø range<br>mm | MBL | Finish     | A<br>mm | B<br>mm | C<br>mm | Ø H<br>mm | Ø P<br>mm | T<br>mm | W<br>mm | D<br>mm | Ø D<br>mm | ØJ mm | L<br>mm | TL<br>mm | TB<br>mm | Weight<br>kg | Delivery time |
|--------------|------------------|--------------------|-----|------------|---------|---------|---------|-----------|-----------|---------|---------|---------|-----------|-------|---------|----------|----------|--------------|---------------|
| 122102200302 | SCS 904 B.SR.GAL | 20-22              | 55  | Galvanized | 107     | 184     | 45      | 26        | 41        | 19      | 44      | 80      | 44        | 77    | 130     | 336      | 123      | 8            | 30            |
| 122102200305 | SCS 904 B.SR     | 20-22              | 55  | Painted    | 107     | 184     | 45      | 26        | 41        | 19      | 44      | 80      | 44        | 77    | 130     | 336      | 123      | 8            | 30            |
| 122102600302 | SCS 905 B.SR.GAL | 23-26              | 75  | Galvanized | 115     | 211     | 60      | 31        | 50        | 22      | 51      | 104     | 52        | 88    | 142     | 386      | 138      | 12           | 30            |
| 122102600305 | SCS 905 B.SR     | 23-26              | 75  | Painted    | 115     | 211     | 60      | 31        | 50        | 22      | 51      | 104     | 52        | 88    | 142     | 386      | 138      | 12           | 30            |
| 122102900302 | SCS 906 B.SR.GAL | 27-29              | 90  | Galvanized | 140     | 215     | 65      | 34        | 57        | 25      | 57      | 114     | 58        | 96    | 159     | 420      | 160      | 16           | 30            |
| 122102900305 | SCS 906 B.SR     | 27-29              | 90  | Painted    | 140     | 215     | 65      | 34        | 57        | 25      | 57      | 114     | 58        | 96    | 159     | 420      | 160      | 16           | 30            |
| 122103200302 | SCS 907 B.SR.GAL | 30-32              | 125 | Galvanized | 150     | 260     | 73      | 36        | 63        | 28      | 63      | 126     | 64        | 110   | 177     | 483      | 165      | 23           | 30            |
| 122103200305 | SCS 907 B.SR     | 30-32              | 125 | Painted    | 150     | 260     | 73      | 36        | 63        | 28      | 63      | 126     | 64        | 110   | 177     | 483      | 165      | 23           | 30            |
| 122103600302 | SCS 908 B.SR.GAL | 33-36              | 125 | Galvanized | 170     | 260     | 73      | 40        | 64        | 28      | 69      | 126     | 68        | 114   | 197     | 503      | 185      | 25           | 30            |
| 122103600305 | SCS 908 B.SR     | 33-36              | 125 | Painted    | 170     | 260     | 73      | 40        | 64        | 28      | 69      | 126     | 68        | 114   | 197     | 503      | 185      | 25           | 30            |

Blueprint

