



Pneumatic vacuum lifters VLA

Product information



For horizontal transport of non-porous, stable and flat sheets of metal, plastic and other materials.

Properties

- VLA types are driven by an pneumatic vacuum pump.

Safety:

- Vacuum protection against release.
- Acoustic signal at negative pressure.
- Safety bar for sufficient distance.
- Pressure gauge, vacuum control.
- Acoustic signal included.
- Rechargeable batteries and charger.
- Minimum air pressure must be 6-7 Bar.

Benefits:

- Ergonomic action by 1 person.
- Low maintenance.

Option

- Manual mechanical rotation and tilting.
- Vacuum lifters for wood and stone on request.
- Higher capacities on request.

IMPORTANT!

- Always check the material specifications and dimensions (L x W x D) of the sheet or workpiece to be lifted.
- Larger tonnages and / or other specifications on request.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

Part Code	GTIN No.	WLL ton	Model	Suction pads quantity / Size mm	Construction height mm	L x B mm	Weight kg	Delivery time
R3660013	8717365022173	0.25	VLA4F-0.25	4 x 250	620	1750 x 1150	55	2
R3660015	8717365022180	0.5	VLA4F-0.5	4 x 300	620	1750 x 1150	55	2
R3660017	8717365022197	0.5	VLA6F-0.5	6 x 250	620	2200 x 1200	90	2
R3660019	8717365022203	1	VLA6F-1.0	6 x 300	620	2200 x 1200	90	2
R3660021	8717365022210	1	VLA8F-1.0	8 x 250	620	2750 x 1150	150	2
R3660023	8717365022227	1.5	VLA8F-1.5	8 x 300	620	2750 x 1150	150	2