

## Double swivel lifting point Codipro DSP



### Product information

The DSP double swivel lifting point provides the option of adapting other lifting accessories: passing a cable or rope through it, placement of a ring with a large eye for using hooks that are disproportionate to the lifting ring,...

With its double swivel action, the DSP ring can be perfectly aligned with the sling. It consists of a steel ring that has a rotating range of 360°.

#### Features:

- 360° rotation.
- Swiveling under load.
- 180° articulation.
- Control anti-crack on 100% of the product.
- Fatigue test.

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to + 200°C

**Standard:** EN 1677-1

**Safety factor:** 5:1

| Part Code  | WLL<br>ton | diameter     | Torque<br>Nm | Standard<br>mm | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | L1<br>mm | S1<br>mm | S2<br>mm | Weight<br>kg | Delivery time |
|------------|------------|--------------|--------------|----------------|---------|---------|---------|---------|---------|---------|---------|----------|----------|----------|--------------|---------------|
| 4215DSPM8  | 0.4        | M 8 (x1,25)  | 6            | 15             | 33      | 56      | 30      | 19      | 19      | 58      | 9.5     | 15       | 8        | 16       | 0.3          | 3             |
| 4215DSPM10 | 0.7        | M 10 (x1.50) | 10           | 18             | 33      | 56      | 30      | 19      | 19      | 58      | 9.5     | 18       | 8        | 16       | 0.3          | 3             |
| 4215DSPM12 | 1.05       | M 12 (x1.75) | 15           | 21             | 33      | 56      | 30      | 19      | 19      | 58      | 9.5     | 21       | 8        | 16       | 0.3          | 3             |
| 4215DSPM14 | 1.4        | M 14 (x2)    | 30           | 23             | 45      | 81      | 45      | 25      | 27      | 79      | 13      | 23       | 8        | 20       | 0.9          | 3             |
| 4215DSPM16 | 2          | M 16 (x2)    | 50           | 27             | 45      | 81      | 45      | 25      | 27      | 79      | 13      | 27       | 8        | 20       | 0.9          | 3             |
| 4215DSPM18 | 2.3        | M 18 (x2.5)  | 70           | 27             | 45      | 81      | 45      | 25      | 27      | 79      | 13      | 27       | 8        | 20       | 1            | 3             |
| 4215DSPM20 | 2.5        | M 20 (x2.5)  | 100          | 30             | 45      | 81      | 45      | 25      | 27      | 79      | 13      | 30       | 8        | 20       | 1            | 3             |

Blueprint

