



Open Wedge Socket G-6413

Product information

The Green Pin® Open Wedge Socket CP is an open wedge socket with a cotter (split) pin. The socket is made from high tensile steel, while galvanization ensures its long-term durability.

Material: high tensile steel

Marking: According to standard

Temperature range: -20°C up to +200°C

Finish: hot dipped galvanized

Standard: EN 13411-6

Part Code	Rope Ø range mm	MBL ton	Finish	Number	width c mm	diameter eye g mm	diameter pin e mm	length to center pin b mm	thickness side slates f mm	length a	width inside d	Weight kg	Delivery time
121500800242	7-8	8	Galvanized	0.25	51	36	16	110	9	128	18	0.79	30
121501000242	9-10	12	Galvanized	0.5	62	46	21	142	11	165	20.5	1.5	30
121501300242	11-13	20	Galvanized	1	66	57	25	146	12	175	25	2.4	30
121501600242	14-16	25	Galvanized	2	82	70	30	176	15	211	31	4	30
121501900242	18-19	40	Galvanized	3	95	80	35	212	16	252	38	7.4	30
121502200242	20-22	55	Galvanized	4	110	95	41	240	19	288	44	11	30
121502600242	24-26	75	Galvanized	5	130	110	51	274	22	329	51	16	30
121502900242	27-29	90	Galvanized	6	144	130	57	310	25	375	57	22	30
121503200242	30-32	110	Galvanized	7	155	146	64	350	28	423	63	31	30
121503600242	34-36	125	Galvanized	8	163	148	64	400	28	474	69	39	30
121503900242	37-39	150	Galvanized	9	178	153	70	450	30	527	76	50	30
121504200242	40-42	170	Galvanized	10	187	160	76	500	33	580	76	66	30
121504800242	43-48	225	Galvanized	11	226	186	89	550	39	650	89	96	30
121505200242	49-52	280	Galvanized	12	240	194	95	640	46	745	101	130	30
121505800242	54-58	360	Galvanized	13	275	230	108	660	54	785	114	180	30
121506800242	60-68	425	Galvanized	14	300	250	121	835	60	970	127	275	30
121507600242	72-76	460	Galvanized	15	355	270	133	1,000	76	1,150	146	440	30
121508600242	81-86	625	Galvanized	16	375	300	140	1,100	79	1,252	159	510	30

Blueprint

