



Regular Swivel G-7713 - Eye/Eye

Product information

The Green Pin® EE Swivel is a swivel with eye-eye end-fittings. The swivel is made from high tensile steel and can be used under water. Galvanization of the Green Pin® EE Swivel ensures its long-term durability. The swivel is available in a range with a working load limit from 0.4 up to 20.5 ton.

Standard: Generally to US Federal Spec. RR-C-271, Type VII, Class 2.

Certification: Test certificates can be supplied upon request.

Material: High tensile steel, quenched and tempered.

Finish: Hot dipped galvanised.

Safety factor: 5:1

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	Weight kg	Delivery time
422500040030	0.39	6	87	32	18	19	27	75	0.1	7
422500060030	0.57	8	107	41	21	25	32	91	0.18	7
422500100030	1.02	10	131	51	24	32	38	111	0.3	7
422500160030	1.6	13	164	64	33	38	51	138	0.6	2
422500240030	2.4	16	198	76	40	45	61	166	1.13	7
422500330030	3.3	19	221	89	45	51	67	183	1.79	7
422500450030	4.5	22	257	102	53	57	78	213	2.55	7
422500570030	5.7	25	298	114	59	64	86	248	4.06	7
422500820030	8.2	32	357	143	68	80	68	293	8.48	7
422502050030	20.5	38	541	198	110	122	110	465	25.7	7

Blueprint

