



Aluminum Chain Block POWERTEX PACB-S1

Product information

POWERTEX



Extremely small and lightweight aluminum chain block. It weighs only approximately 50% of a similar standard chain block. The block can be used for lifting as well as pulling.

Features:

- Safe Each block is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction with aluminum covers
- Durable construction with powder coated finish and plated frame parts
- Chain block is chromium 6 free
- · Sealed bearings on the chain wheel maximize efficiency and serviceability.
- Sprocket wheel surface treated against wear and corrosion
- Safe and well covered automatic load reaction break
- Equipped with double brake pawls
- Fine calibrated European made load chain for smooth operation
- · Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- · Hook have Deformation Check Dots forged into side for overload detection
- RFID (chip) equipped for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- · Test certificate and Declaration of Conformity enclosed with each hoist
- 14 language User Manual enclosed with each hoist
- Spare parts available

Material: Durable aluminium/steel construction

Marking: According to standard, CE-marked, POWERTEX, Model, WLL, Chain type , Serial number, User manual/QR code Temperature range: -10°C up to +50°C

Finish: White powder coated body, side plate assembly and hooks black powder coated Standard: EN 13157, EN 818-7

Safety factor: 4:1

Part Code	WLL ton	Lifting height m	Model	Load chain mm	Hand chain mm	Number of falls	Hand force max. kg	Hand chain length m	A B mm mr					Weight kg	Delivery time
500100030300170	0.25	3	PACB-S1/250	3,0 x 9	2,5 x 12	1	15	2,5	75 77	' 44	32 3	5.5 21	225	2.6	7
500100030600170	0.25	6	PACB-S1/250	3,0 x 9	2,5 x 12	1	15	2.5	75 77	' 44	32 3	5.5 21	225	3.8	7
500100050300170	0.5	3	PACB-S1/500	4,0 x 12	3,5 x 16	1	19	2,5	92 89	51	34.5	2 23	265	4.6	7
500100050600170	0.5	6	PACB-S1/500	4,0 x 12	3,5 x 16	1	19	2.5	92 89) 51	34.5	2 23	265	6.1	7
500100100300170	1	3	PACB-S1/1000	5,6 x 15,7	3,5 x 16	1	29	2,5	110 10	2 55	42.5 4	9.5 27	295	6.6	7
500100100600170	1	6	PACB-S1/1000	5,6 x 15,7	3,5 x 16	1	29	2.5	110 10	2 55	42.5 4	9.5 27	295	10.14	7
500100200300170	2	3	PACB-S1/2000	8,0 x 24	4,8 x 22	1	37	2,5	145 13	8 78.5	46.5 5	3.5 35	390	13.5	7
500100200600170	2	6	PACB-S1/2000	8,0 x 24	4,8 x 22	1	37	2.5	145 13	8 78.5	46.5 5	3.5 35	390	20.4	7
500100300300170	3	3	PACB-S1/3000	7,1 x 20,1	4,8 x 22	2	35	2,5	165 12	0 68	50 6	L.9 37	470	17	7
500100300600170	3	6	PACB-S1/3000	7,1 x 20,1	4,8 x 22	2	35	2.5	165 12	0 68	50 6	L.9 37	470	26.3	7

Blueprint

