



Super Reeve Connector Swivel Sockets SCS-SW - with pin

Product information

- Dimensional tolerances depend on the manufacturing techniques applied and are different between machined components (pins) and cast components (socket bodies and wedges).
- All sockets are provided with an EN 10204-2.1 declaration of conformity, EN 10204-3.1 material certificate and can be provided with a 2006/42/EC declaration where applicable.
- Also surface finish e.g. hot dip galvanizing may add to the overall thickness and fork distance.

Material: Quenched and tempered cast steel.

Finish: Hot dipped galvanized.

Part Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	D mm	G mm	N mm	L mm	T mm	TB mm	TL mm	Ø D mm	Ø H mm	Ø J mm	Ø P mm	W mm	Weight kg	Delivery time
122101600272	13-16	25	Galvanized	182	157	32	58	60	76	98	14	85	371	32	19	56	30	32	7	7
122101900272	16-19	40	Galvanized	208	186	40	70	70	93	114	16	95	434	40	22	65	35	38	11	7
122102200272	20-22	55	Galvanized	238	208	45	80	80	105	130	19	110	491	44	26	77	41	44	17	7
122102600272	23-26	75	Galvanized	266	235	60	98	96	125	142	22	128	561	52	31	88	50	51	26	7
122102900272	27-29	90	Galvanized	290	262	65	108	107	135	159	25	142	617	58	34	96	57	57	34	7
122103200272	30-32	125	Galvanized	327	292	73	120	118	150	177	28	155	692	64	36	110	63	63	49	7

Blueprint

