



General use



Stay rope



Agriculture and livestock



Steel Wire Rope ROPETEX S49 Stainless Steel

Product information

ROPETEX



SZ

SS



ROPETEX S49 in stainless steel is a wire rope often used as stay rope, stående rigging, hanging signs, and fencing rope.

Due to its high quality stainless steel material grade it has an excellent corrosion resistance. It's most used in small diameters up to 12 mm.

ROPETEX S49 is equipped with a steel core (WSC).

Rope construction: 6x7-WSC (7x7)

Material: AISI 316 / EN 1.4401

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-4

except material

Warning: Not to be used for lifting purposes

Fill factor: 0,55

Part Code	Rope Diameter, mm	Steel area mm ²	Min. Breaking force kN. 1570 N/mm ²	Weight kg/100m
108100104620028	1	0.43	0.61	0.38
108100124620028	1.2	0.62	0.88	0.55
108100154620028	1.5	0.97	1.37	0.86
108100204620028	2	1.73	2.44	1.54
108100304620028	3	3.89	5.48	3.46
108100404620028	4	6.91	9.75	6.14
108100504620028	5	10.8	15.2	9.6
108100604620028	6	15.6	21.9	13.8
108100804620028	8	27.6	39	25