



Dee Shackles with Screw Collar Pin G-4151

Product information

Dee shackle with screw collar pin.

Certification: This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Standard: EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVB Class 2, Grade A.

Material: Bow and pin high tensile steel, quenched and tempered

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C

Finish: Hot dip galvanized

Standard: EN 13889

Safety factor: 6:1

Grade: 6

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	Weight kg	Delivery time
420100030680	0.33	5	6	12	5	9,5	19	33	29,5	0.02	7
420100050680	0.5	7	8	16,5	7	12	22	41,5	38	0.05	2
420100080680	0.75	9	10	20	9	13,5	26	50	46,5	0.09	2
420100100680	1	10	11	22,5	10	17	32	59	54	0.14	2
420100150680	1.5	11	13	26,5	11	19	37	68	59,5	0.19	2
420100200680	2	13,5	16	34	13	22	43	81	73	0.32	2
420100330680	3.25	16	19	40	16	27	51	97	89	0.54	2
420100480680	4.75	19	22	46	19	31	59	112	103	0.87	2
420100650680	6.5	22	25	52	22	36	73	134	119	1.34	7
420100850680	8.5	25	28	59	25	43	85	154	137	2.08	2
420100950680	9.5	28	32	66	28	47	90	167	153	2.77	2
420101200680	12	32	35	72	32	51	94	180	170	3.72	2
420101350680	13.5	35	38	80	35	57	115	209	186	5.14	7
420101700680	17	38	42	88	38	60	127	230	203	6.85	7
420102500680	25	45	50	103	45	74	149	271	243	11.45	7
420103500680	35	50	57	111	50	83	171	305	272	16.86	7
420104250680	42.5	57	65	130	57	95	190	345	310	24.61	7
420105500680	55	65	70	145	65	105	203	376	344	32.65	7

Blueprint

