

Rope Socket Demag

Product information



¹⁾ Wire rope Diameter in acc. to DIN EN 12385 (former DIN 3051 – 3071).

²⁾ For socketing only use the following materials: DF-VM Art. Nr. 01-7016010, TEGO VG3 Art. Nr. 01-7016028, or Wirelock. Please obtain the socketing guidelines 20612044 (720 IS 817) and DIN EN 13411-4. Socketing Materials´ have the aproval from the Germanischen Lloyd. Weight for socketing material are listed for 1 socket.

⁴⁾ Delivery time on request.

Don't use ropes with bigger diameter as listed in the chart even NOT when the dimension "d" in the chart allows the use of bigger rope diameters.

Material: Permanent rope connectors make it possible to change load handling attachments quickly by simply detaching and connecting the grab ropes to the closing ropes on the hoist unit.

Marking: Producer, Size, Batch No.

Part Code	Rope Ø range mm	G mm	Nom. size	Allowable_dim.	Potting kg ²</SUP>	Beak roll diameter m min. mm	A mm	D mm	e mm	f mm	r mm	Weight kg	Delivery time
122101800020	18	19,5	5	1.5	0,723	560	114	20	84	21	245	1.3	7
122102000020	19-20	21,5	6	2	0,78	630	129	22	84	23	310	1.6	7
122102400020	22-24	23,5	7	2	1,36	710	140	26	100	26	310	2.4	7
122102600020	26	25,5	8	2	1,4	800	158	29	100	28	350	2.6	7
122102800020	28	27,5	9	2	2,3	900	171	31	120	31	350	3.6	7
122103200020	32	29	10	2	2,65	1,000	190	35	120	32	445	4.4	2
122103500020	35	31	11	2	4,3	1,120	203	37	142	36	445	6	7
122103600020	36	35	12	2.5	4,1	1,120	225	40	142	39	495	7.5	7
122104000020	40	37	13	2.5	6,5	1,250	242	43	166	43	555	9	7
122104800020	48	43	15	2.5	6,7	1,600	286	51	166	49	595	12.5	7
122106400020	64	60	17	2.5	10,0	2,100	400	75	250	75	950	30	7