



Coil Hook Type CH

Product information



This type of coil hook is designed for lifting and handling of steel coils or other heavy materials. The suspension eye is placed at the centre of gravity meaning that the coil hook will always be in balance with or without load. If used correctly the coil hook will never tilt forward therefor eliminating the risk of unintended loss of the coil.

Coil hooks type CH are available in various sizes with a permissible load range from 5.000 kg to 30.000 kg.

Design: Lightweight welded beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Part Code	WLL ton	Max coil width mm	Type	L mm	L1 mm	L2 mm	H mm	H1 mm	H2 mm	Weight kg	Delivery time
503500501050070	5	1,050	CH 5 / 1,05-0,55	1,230	1,050	545	1,060	890	550	299	7
503500501270070	5	1,270	CH 5 / 1,27-0,55	1,470	1,270	655	1,100	910	550	371	7
503500501540070	5	1,540	CH 5 / 1,54-0,55	1,760	1,540	790	1,140	930	550	455	7
503501001050070	10	1,050	CH 10 / 1,05-0,65	1,290	1,050	545	1,290	1,070	650	546	7
503501001270070	10	1,270	CH 10 / 1,27-0,65	1,530	1,270	655	1,330	1,090	650	635	7
503501001540070	10	1,540	CH 10 / 1,54-0,65	1,820	1,540	790	1,370	1,110	650	752	7
503501501050070	15	1,050	CH 15 / 1,05-0,70	1,370	1,050	545	1,520	1,230	700	790	7
503501501270070	15	1,270	CH 15 / 1,27-0,70	1,610	1,270	655	1,560	1,250	700	902	7
503501501540070	15	1,540	CH 15 / 1,54-0,70	1,850	1,540	790	1,500	1,220	700	988	7
503502001050070	20	1,050	CH 20 / 1,05-0,80	1,380	1,050	545	1,680	1,390	800	1,021	7
503502001270070	20	1,270	CH 20 / 1,27-0,80	1,620	1,270	655	1,720	1,410	800	1,142	7
503502001540070	20	1,540	CH 20 / 1,54-0,80	1,910	1,540	790	1,760	1,430	800	1,298	7
503503001050070	30	1,050	CH 30 / 1,05-0,95	1,450	1,050	545	1,980	1,640	950	1,596	7
503503001270070	30	1,270	CH 30 / 1,27-0,95	1,690	1,270	655	2,020	1,660	950	1,734	7
503503001540070	30	1,540	CH 30 / 1,54-0,95	1,980	1,540	790	2,040	1,680	950	1,912	7

Blueprint

