

Lifting Beam Type H

Product information



This type of lifting beam cannot be adjusted and is designed for direct attachment with the crane hook in the central lifting eye. The lifting beam is designed with one attachment point in each corner and is based on lifting assignments in all four points. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Material: Hollow beam and plate manufactured with high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Part Code	Code	WLL	H mm	L1 mm	L2 mm	Weight kg	Delivery time
62056410051500	H-0,5/2-1,5	0.5	255	2,000	1,500	80	7
62056410052000	H-0,5/3-2	0.5	255	3,000	2,000	109	7
62056410052500	H-0,5/4-2,5	0.5	255	4,000	2,500	152	7
62056410151500	H-1,5/2-1,5	1.5	310	2,000	1,500	102	7
62056410152000	H-1,5/3-2	1.5	310	3,000	2,000	139	7
62056410152500	H-1,5/4-2,5	1.5	310	4,000	2,500	216	7
62056410301500	H-3/2-1,5	3	395	2,000	1,500	131	7
62056410302000	H-3/3-2	3	395	3,000	2,000	185	7
62056410302500	H-3/4-2,5	3	395	4,000	2,500	263	7
62056410501500	H-5/2-1,5	5	440	2,000	1,500	193	7
62056410502000	H-5/3-2	5	440	3,000	2,000	275	7
62056410502500	H-5/4-2,5	5	440	4,000	2,500	388	7
62056410801500	H-8/2-1,5	8	555	2,000	1,500	326	7
62056410802000	H-8/3-2	8	555	3,000	2,000	422	7
62056410802500	H-8/4-2,5	8	555	4,000	2,500	565	7
62056411001500	H-10/2-1,5	10	720	2,000	1,500	502	7
62056411002000	H-10/3-2	10	720	3,000	2,000	647	7
62056411002500	H-10/4-2,5	10	720	4,000	2,500	793	7

Blueprint

