

Lifting Beam Type H-SB

Product information



This type of lifting beam has adjustable attachment points in one direction via a cam beam and is based on lifting in four points. The lifting beam is designed for direct attachment with the crane hook in the central lifting eye. The attachment points are designed as oval rings, which makes it possible to use for example a 2-part sling. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded beam construction providing good torsional stiffness.

Proof load: Usualley 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Part Code	Code	WLL ton	H mm	L1 mm	L2 mm	Weight kg	Delivery time
62056420051500	H-SB-0,5/2-1,5	0.5	280	2,000	1,500	97	7
62056420052000	H-SB-0,5/3-2	0.5	280	3,000	2,000	143	7
62056420052500	H-SB-0,5/4-2,5	0.5	280	4,000	2,500	173	7
62056420151500	H-SB-1,5/2-1,5	1.5	330	2,000	1,500	135	7
62056420152000	H-SB-1,5/3-2	1.5	330	3,000	2,000	178	7
62056420152500	H-SB-1,5/4-2,5	1.5	330	4,000	2,500	256	7
62056420301500	H-SB-3/2-1,5	3	415	2,000	1,500	165	7
62056420302000	H-SB-3/3-2	3	415	3,000	2,000	224	7
62056420302500	H-SB-3/4-2,5	3	415	4,000	2,500	302	7
62056420501500	H-SB-5/2-1,5	5	455	2,000	1,500	229	7
62056420502000	H-SB-5/3-2	5	455	3,000	2,000	320	7
62056420502500	H-SB-5/4-2,5	5	455	4,000	2,500	428	7
62056420801500	H-SB-8/2-1,5	8	595	2,000	1,500	422	7
62056420802000	H-SB-8/3-2	8	595	3,000	2,000	524	7
62056420802500	H-SB-8/4-2,5	8	595	4,000	2,500	667	7
62056421001500	H-SB10/2-1,5	10	760	2,000	1,500	609	7
62056421002000	H-SB-10/3-2	10	760	3,000	2,000	760	7
62056421002500	H-SB10/4-2,5	10	760	4,000	2,500	906	7

Blueprint

