

Beam Clamp - IPBHZ



Product information

General:

The IPBHZ beam clamp is used for horizontal lifting and transferring of steel beams. The base is slotted to allow the clamps to be used from end of beams as well as from the flange. This series of clamps can be used in vertical and horizontal moving, transferring and stacking of different types of structural designs, such as I-Beams, H-beams, angles, etc, depending on the application desired.

Features:

- Available in capacities of .75 thru 12 metric tons.
- Wide variety of jaw openings available from 75 to 40 mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Warning: A minimum load of 10% of the WLL is required.

Part Code	WLL ton	Jaw width mm	I P Model.	B mm	C mm	D mm	E mm	F mm	G mm	J mm	L mm	Weight kg	Delivery time
502100080250200	0.75	0-25	0.75-IPBHZ	40	148	220	50	130	69	33	22	3	7
502100150250200	1.5	0-25	1.5-IPBHZ	60	203	255	50	158	73	35	28	6	7
502100300400200	3	0-40	3-IPBHZ	80	227	325	70	188	112	38	32	10.5	7
502100450400200	4.5	0-40	4.5-IPBHZ	112	284	413	70	251	116	80	40	25	7
502101200400200	12	0-40	12-IPBHZ	125	466	490	90	317	90	90	47	42.3	7

Blueprint

