



Beam Clamp IPSTARTEC11

Product information

General:

The IPSTARTEC11 beam clamp has been specially developed for lifting with the body in vertical position, controlled tilting, transportation and stacking of steel "H" and "I" profiles. By placing the chain guide in the appropriate position, it is easy to switch from lifting to tilting and back again, which shifts the center of gravity.

Features:

- Available in capacities of 1.5 and 2.5 metric tons.
- Jaw openings available: 6 to 20mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Features:

Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Part Code	WLL ton	Jaw width mm	I P Model.	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	Weight kg	Delivery time
502100150120240	1.5	6-12	1.5-IPSTARTEC11	140	39	575	110	81	129	54	126	16	6.6	7
502100250200240	2.5	6-20	2.5-IPSTARTEC11	210	55	725	135	115	182	74	140	18	14.5	7

Blueprint

