



Closed Spelter Socket G-417

Product information

McKissick Closed spelter socket for steel wire rope $\varnothing$ 8 mm up to $\varnothing$ 102 mm. Spelter socket terminations have an efficiency rating of 100%, based on the catalogue strength of wire rope.

Features:

- Forged Steel Sockets through 38 mm, cast alloy steel 40 mm through 102mm.
- All cast steel sockets 40 mm and larger are magnetic particle inspected and ultrasonic inspected.
- Proof testing available on special order.
- Spelter socket terminations have an efficiency rating of 100%, based on the catalog strength of wire rope.
- Ratings are based on recommended use with 6x7, 6x19, or 6x37, IPS or XIP (EIP), XXIP (EEIP), RRL, FC, or IWRC wire rope.
- Strand constructed with minimal number of wires (e.g. 1x7) requires special consideration that socket basket length be five (5) times the strand diameter or fifty (50) times the wire diameter, whichever is the greater.
- Also available in self-coloured / ungalvanized version on request.

Standard: Fed Spec RR-S-550D TYPE B.

Material: Forged steel from wire rope $\varnothing$ 8mm up to 38mm. From $\varnothing$ 40mm Cast Alloy steel.

Marking: ID code and Manufacturer's symbol.

Finish: Galvanized.

Safety factor: 5:1

Part Code	Rope Ø range mm	WLL ton	Finish	Rope dia. inch	A mm	B mm	C mm	D* mm	F mm	G mm	H mm	J mm	K mm	L mm	Weight kg	Delivery time
122101000052	8-10	12	Galvanized	5/6 -3/8	125	15.8	42.9	24.6	12.7	20.6	42.9	57.2	17.5	52.5	0.34	7
122101300052	11-13	20	Galvanized	7/16-1/2	140	17.5	51	29.5	14.2	23.9	51	63.5	22.4	58.7	0.68	7
122101600052	14-16	30.8	Galvanized	9/16-5/8	162	20.6	67	35.8	17.5	30.2	67	76.2	25.4	65	1.13	7
122101800052	18	43.5	Galvanized	3/4	194	26.9	76.2	42.2	22.4	33.3	70	89	31.8	77.5	1.92	7
122102200052	20-22	65.3	Galvanized	7/8	226	33.3	92	49.3	25.4	38.1	82.5	102	38.1	90.5	3.28	7
122102600052	24-26	81.6	Galvanized	1	254	36.6	105	58.5	28.7	44.5	95.5	114	44.5	103	4.76	7
122103000052	28-30	100	Galvanized	1 1/8	283	39.6	114	65	31.8	51	105	127	51	116	6.46	7
122103500052	32-35	136	Galvanized	1 1/4-1 3/8	309	41.4	127	71	38.1	58.5	119	138	56.5	129	8.95	7
122103800052	38	170	Galvanized	1 1/2	355	49.3	137	81	41.4	70.5	132	151	62.5	155	13.2	7
122104200052	40-42	188	Galvanized	1 5/8	390	54	146	82.5	44.5	76.2	140	165	70	171	16.3	7
122104800052	44-48	268	Galvanized	† 1 3/4-1 7/8	445	55.5	171	95.5	51	79.5	162	191	76.2	198	26	7
122105400052	50-54	309	Galvanized	† 2-2 3/8	505	62	194	111	57.2	95.5	187	216	82.5	224	35.8	7
122106000052	56-60	360	Galvanized	† 2 1/4 - 2 3/8	546	70	216	127	66.8	105	210	229	92	254	47.6	7
122106700052	64-67	424	Galvanized	† 2 1/2 - 2 7/8	597	79.5	241	140	74.5	114	235	248	102	270	64	7
122107300052	70-73	549	Galvanized	† 2 3/4 - 2 7/8	645	79.5	273	159	79.5	124	259	279	124	286	100	7
122108000052	75-80	656	Galvanized	† 3 - 3 1/8	689	85.6	292	171	86	133	292	305	133	298	125	7
122108600052	82-86	750	Galvanized	† 3 1/4 - 3 3/8	743	102	311	184	92	146	311	330	146	311	142	7
122109200052	88-92	820	Galvanized	† 3 1/2 - 3 5/8	787	102	330	197	98.5	165	330	356	159	330	181	7
122110200052	94-102	1,005	Galvanized	† 3 3/4 - 4	845	108	362	216	108	184	362	381	178	356	246	7

Blueprint

