



## Master Link Assemblies G/S Grade 10

### Product information

Master link sub-assembly.

**Material:** Alloy steel

**Marking:** Code and grade.

**Finish:** Violet powder coated.

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Code      | Chain diameter | WLL ton | Chain mm | d mm | d1 mm | e mm | t mm | t1 mm | s mm | w mm | w1 mm | Weight kg | Delivery time |
|--------------|-----------|----------------|---------|----------|------|-------|------|------|-------|------|------|-------|-----------|---------------|
| 402100420250 | G/S-6     | -              | 4.2     | 6        | 19   | 13    | 189  | 135  | 54    | 10   | 75   | 25    | 1.28      | 2             |
| 402100760250 | G/S-7/8   | -              | 7.6     | 7+8      | 23   | 17    | 230  | 160  | 70    | 14   | 90   | 34    | 2.37      | 2             |
| 402100960250 | G/S-10    | -              | 9.6     | 10       | 27   | 20    | 265  | 180  | 85    | 14   | 100  | 40    | 3.75      | 2             |
| 402101400250 | G/S-13    | -              | 14      | 13       | 33   | 23    | 315  | 200  | 115   | 17   | 110  | 50    | 6.6       | 2             |
| 402102120250 | G/S-16    | -              | 21.2    | 16       | 36   | 27    | 400  | 260  | 140   | 20   | 140  | 65    | 10.06     | 2             |
| 402103410250 | G/S-19/20 | 6              | 34.1    | 19       | 50   | 33    | 500  | 350  | 150   | 26   | 190  | 70    | 22.87     | 7             |
| 402104000250 | G/S-22    | -              | 40      | 22       | 50   | 36    | 520  | 350  | 170   | -    | 190  | 75    | 24.79     | 7             |
| 402105600250 | G/S-26    | -              | 56      | 26       | 56   | 45    | 570  | 400  | 170   | -    | 200  | 80    | 37.6      | 7             |

## Blueprint

