



Master Link Pewag AWI Stainless

Product information



Stamped and suitable for both I- and II-leg assemblies and wire rope slings (similar to DIN 3088- 1989). The master link may also be used in VWI four-leg assemblies and as an end link. Its dimensions are similar to DIN 5688-1 and it is tested at 100 % of its load capacity.

A particular bonus is the higher resistance to acids and caustics compared to the standard loading rings G8, G10 and G12.

The AWI Master link is particularly suited for use in water and wastewater applications. It can also be used in connection with chemicals and food products; however, restrictions will apply.

Material: 1.4404 (AISI 316L), 1.4462 (AISI 318LN).

Marking: CE-marked

Finish: Pickled and blasted.

Safety factor: 4:1

Grade: 6

Part Code	Code	WLL ton	Usable with sling hooks up to DIN 15401 No.	For chain Ø 1-leg mm	For chain Ø 2-leg mm	Double hook DIN 15402 no.	d mm	t mm	w mm	s mm	Weight kg	Delivery time
400100850050	AWI 10-6	0.85	1.6	5	5	2.5	10	80	50	-	0.16	7
400100160050	AWI 13-6	1.6	2.5	6/7/8	6	4	13	110	60	10	0.34	7
400100260050	AWI 16-6	2.6	2.5	10	7/8	4	16	110	60	14	0.53	7
400100350050	AWI 18-6	3.5	5	-	10	6	18	135	75	14	0.83	7
400100630050	AWI 22-6	6.3	6	13/16	13	8	23	160	90	17	1.55	7
400100890050	AWI 26-6	8.9	8	20	16	10	27	180	100	20	2.46	7
400101320050	AWI 32-6	13.2	10	-	20	12	32	200	110	26	3.86	7
400101470050	AWI 36-6	14.7	16	-	-	20	36	260	140	29	6.22	7

Blueprint

