


Ropetex 55

Product information



ROPETEX



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope. Flexibility is optimised by the unique strand and rope construction. Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

RopeTex Ropes are lubricated with the very latest High Performance Wire rope lubricants to give excellent corrosion protection, fatigue life combined with low fling off

ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Features: Very High Breaking Load

Material: High Carbon Steel

Marking: According to standard

Finish: Galvanised as standard

Standard: EN 12385-4

Fill factor: 0,64

RCN: 23-1

Part Code	Rope Diameter,	Min. Breaking force kN. 2160 N/mm²	Breaking Load ton	Weight kg/100m
102100806300069	8	50.5	5.15	27.6
102100906300069	9	64	6.52	34.4
102101006300069	10	79	8.05	43
102101106300069	11	95.6	9.75	52
102101206300069	12	114	11.62	62
102101306300069	13	134	13.66	72
102101406300069	14	155	15.8	84
102101506300069	15	178	18.14	96
102101606300069	16	202	20.6	110
102101706300069	17	228	23.2	120
102101806300069	18	256	26.1	135
102101906300069	19	285	29.1	150
102102006300069	20	316	32.2	166
102102206300069	22	382	38.94	201
102102406300069	24	455	46.38	245
102102606300069	26	527	53.72	297
102102806300069	28	612	62.38	345