



Standard Reeve Crane Blocks 2 Sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part Code	WLL ton	Model no.	For wire Ø mm	Hooksize	Ø D1 mm	Ø D2 mm	B mm	O mm	TA mm	TB mm	TL mm	L mm	T mm	Ø Z mm	Weight kg	Delivery time
6097SRB28516216E	16	SRB 285 .16 .2 .16 .E	16	6	320	280	608	59	420	165	908	1,033	28	32	95	7
6097SRB26014216E	16	SRB 260 .14 .2 .16 .E	14	6	300	260	593	59	400	166	878	1,003	28	32	130	7
6097SRB26016216E	16	SRB 260 .16 .2 .16 .E	16	6	300	260	593	59	400	166	878	1,003	28	32	130	7
6097SRB28516220EA	20	SRB 285 .16 .2 .20 .E .A	16	8	320	280	668	69	420	165	968	1,103	28	32	130	7
6097SRB28516220EB	20	SRB 285 .16 .2 .20 .E .B	16	8	320	280	668	69	420	195	968	1,103	28	32	150	7
6097SRB32016220E	20	SRB 320 .16 .2 .20 .E	16	8	365	320	688	69	450	195	1,011	1,146	28	32	160	7
6097SRB32016225E	25	SRB 320 .16 .2 .25 .E	16	8	365	320	688	69	450	240	1,011	1,146	28	32	205	7
6097SRB35519229E	29	SRB 355 .19 .2 .29 .E	19	8	410	355	713	69	500	245	1,063	1,203	35	37	250	7
6097SRB40022229E	29	SRB 400 .22 .2 .29 .E	22	8	460	400	743	69	570	250	1,128	1,273	40	43	320	7
6097SRB45024240E	40	SRB 450 .24 .2 .40 .E	24	12	515	450	894	84	600	333	1,322	1,477	45	52	550	7
6097SRB45026250E	50	SRB 450 .26 .2 .50 .E	26	16	515	450	894	97	600	333	1,322	1,514	45	52	550	7
6097SRB52826263E	63	SRB 528 .26 .2 .63 .E	26	16	595	528	1,003	97	710	403	1,483	1,675	45	52	980	7
6097SRB52828280E	80	SRB 528 .28 .2 .80 .E	28	20	595	528	1,109	110	710	413	1,589	1,809	50	59	1,000	7
6097SRB670282100E	100	SRB 670 .28 .2 .100 .E	28	20	760	670	1,257	110	870	502	1,822	2,042	50	59	2,240	7
6097SRB670322100E	100	SRB 670 .32 .2 .100 .E	32	20	760	670	1,257	110	870	502	1,822	2,047	60	66	2,240	7

Blueprint

