



Standard Reeve Crane Blocks 3 Sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part Code	WLL ton	Model no.	For wire Ø mm	Hooksize	Ø D1 mm	Ø D2 mm	B mm	O mm	TA mm	TB mm	TL mm	L mm	T mm	Ø Z mm	Weight kg	Delivery time
6097SRB26014325E	25	SRB 260 .14 .3 .25 .E	14	8	300	260	658	69	400	260	953	1,088	28	32	210	7
6097SRB26016325E	25	SRB 260 .16 .3 .25 .E	16	8	300	260	658	69	400	260	953	1,088	28	32	210	7
6097SRB28516329E	29	SRB 285 .16 .3 .29 .E	16	8	325	285	668	69	400	270	978	1,113	28	32	210	7
6097SRB32016329E	29	SRB 320 .16 .3 .29 .E	16	8	365	320	713	69	450	240	1,048	1,183	28	32	225	7
6097SRB35519332E	32	SRB 355 .19 .3 .32 .E	19	10	410	355	753	76	500	262	1,093	1,244	35	37	325	7
6097SRB36019340E	40	SRB 360 .19 .3 .40 .E	19	12	410	360	839	84	500	362	1,179	1,342	35	37	455	7
6097SRB40022340E	40	SRB 400 .22 .3 .40 .E	22	12	460	400	864	84	570	353	1,244	1,412	40	43	500	7
6097SRB40022350E	50	SRB 400 .22 .3 .50 .E	22	16	460	400	864	97	570	353	1,244	1,426	40	43	500	7
6097SRB40022350E	50	SRB 400 .22 .3 .50 .E	22	16	460	400	864	97	570	373	1,244	1,426	40	43	540	7
6097SRB45022363E	63	SRB 450 .22 .3 .63 .E	22	16	515	450	963	97	600	343	1,376	1,558	40	43	680	7
6097SRB45024363E	63	SRB 450 .24 .3 .63 .E	24	16	515	450	963	97	600	383	1,376	1,568	45	52	770	7
6097SRB45026363E	63	SRB 450 .26 .3 .63 .E	26	16	515	450	963	97	600	383	1,376	1,568	45	52	770	7
6097SRB52826380E	80	SRB 528 .26 .3 .80 .E	24	20	595	528	1,132	110	710	462	1,612	1,822	45	52	1,270	7
6097SRB52826380E	80	SRB 528 .26 .3 .80 .E	26	20	595	528	1,132	110	710	462	1,612	1,822	45	52	1,270	7
6097SRB528263100E	100	SRB 528 .26 .3 .100 .E	26	25	595	528	1,223	132	710	462	1,683	1,913	45	52	1,270	7
6097SRB528283100E	100	SRB 528 .28 .3 .100 .E	28	25	595	528	1,223	132	710	462	1,683	1,923	50	59	1,270	7
6097SRB670283125E	125	SRB 670 .28 .3 .125 .E	28	25	760	670	1,353	132	870	642	1,918	2,158	50	59	2,900	7
6097SRB670323125E	125	SRB 670 .32 .3 .125 .E	32	25	760	670	1,353	132	870	642	1,918	2,163	60	66	2,900	7

Blueprint

