

Spannschloss, Öse/Öse Ropeblock

Produktinformation

Allgemein:

- Feuerverzinkt
- Inklusive Sicherungsmutter
- Hochfester Stahl (geschmiedet)
- MBL = 5x WLL



Artikel-Nr.	Tragfähigkeit t	Gewinde mm	Thread Inch	Aufnahme (mm)	L min.	L max.	A mm	J mm	K mm	L mm	Gewicht (kg)	Lieferzeit (in Tagen)
422100230240	0,23	6,35	1/4	102	198	300	121	6	9	20	0,12	30
422100360240	0,36	7,94	5/16	114	230	344	138	8	11	24	0,2	30
422100540240	0,54	9,53	3/8	152	291	444	181	9	13	28	0,34	30
422100100240	1	12,7	1/2	152	332	510	191	11	18	37	0,7	30
422100100245	1	12,7	1/2	229	409	614	266	11	18	37	0,77	30
422100100246	1	12,7	1/2	305	485	815	343	11	18	37	0,97	30
422100160245	1,59	15,9	5/8	229	450	655	276	13	22	44	1,32	30
422100160240	1,59	15,9	5/8	152	373	557	200	13	22	44	1,49	14
422100160246	1,59	15,9	5/8	305	525	862	353	13	22	44	1,55	30

422100240240	2,36	19,1	3/4	152	416	607	210	16	25	53	1,72	30
422100240245	2,36	19,1	3/4	229	492	697	286	16	25	53	1,92	30
422100240246	2,36	19,1	3/4	305	568	911	362	16	25	53	2,49	30
422100240247	2,36	19,1	3/4	457	721	1.216	514	16	25	53	3,26	30
422100330240	3,27	22,2	7/8	305	592	942	370	19	32	60	3,27	30
422100330245	3,27	22,2	7/8	457	745	1.246	523	19	32	60	4,51	30
422100450245	4,54	25,4	1	152	507	710	228	23	36	76	4,1	30
422100450247	4,54	25,4	1	305	660	1.015	380	23	36	76	5,22	30
422100450246	4,54	25,4	1	457	812	1.320	532	23	36	76	6,35	30
422100450240	4,54	25,4	1	610	964	1.625	685	23	36	76	7,82	30
422100690240	6,89	31,8	1-1/4	305	719	1.087	384	29	46	90	8,62	30
422100690245	6,89	31,8	1-1/4	457	871	1.392	537	29	46	90	10,4	30
422100690246	6,89	31,8	1-1/4	610	1.024	1.697	689	29	46	90	12,2	30
422100970240	9,71	38,1	1-1/2	305	775	1.156	400	32	54	103	12,5	30
422100970245	9,71	38,1	1-1/2	457	927	1.461	553	32	54	103	14,1	30
422100970246	9,71	38,1	1-1/2	610	1.080	1.765	705	32	54	103	17	30
422101270240	12,7	44,5	1-3/4	457	1.000	1.457	568	38	60	117	23,8	30
422101270245	12,7	44,5	1-3/4	610	1.153	1.762	721	38	60	117	26,3	30
422101680240	16,8	51	2	610	1.313	1.923	738	45	68	146	8,7	30
422102720240	27,2	63,5	2-1/2	610	1.387	1.997	789	51	79	165	65	30
422103400240	34	70	2-3/4	610	1.448	2.057	788	57	82	177	88	30

Blaupause

