

# Spannschloss, Gabel/Öse Ropeblock

## Produktinformation

### Allgemein:

- Feuerverzinkt
- Inklusive Sicherungsmutter
- Hochfester Stahl (geschmiedet)
- MBL = 5x WLL



Artikel-Nr.	Tragfähigkeit t	Gewinde mm	Thread Inch	Aufnahme (mm)	L min.	L max.	A mm	I mm	K mm	L mm	P mm	U (mm)	W mm	Gewicht (kg)	Lieferzeit (in Tagen)
422100230230	0,23	6,35	1/4	102	187	288	121	6	9	20	6	15	11	0,14	30
422100360230	0,36	7,94	5/16	114	221	348	138	8	11	24	6	22	13	0,23	30
422100540230	0,54	9,53	3/8	152	275	427	181	9	13	28	8	22	14	0,36	30
422100100230	1	12,7	1/2	152	312	490	190	11	18	37	10	27	16	0,68	30
422100100235	1	12,7	1/2	229	388	642	266	11	18	37	10	27	16	0,78	30
422100100236	1	12,7	1/2	305	465	795	343	11	18	37	10	27	16	0,94	30
422100160230	1,59	15,9	5/8	152	349	533	200	13	22	44	13	33	20	1,07	30
422100160235	1,59	15,9	5/8	229	425	686	276	13	22	44	13	33	20	1,44	30
422100160236	1,59	15,9	5/8	305	501	838	353	13	22	44	13	33	20	1,64	30

422100240230	2,36	19,1	3/4	152	390	575	210	16	25	53	16	38	24	1,81	30
422100240235	2,36	19,1	3/4	229	470	730	286	16	25	53	16	38	24	2,15	30
422100240236	2,36	19,1	3/4	305	540	880	362	16	25	53	16	38	24	2,69	30
422100240237	2,36	19,1	3/4	457	691	1.186	514	16	25	53	16	38	24	3,18	30
422100330230	3,27	22,2	7/8	305	567	917	307	19	32	60	19	44	29	3,79	30
422100330235	3,27	22,2	7/8	457	720	1.220	523	19	32	60	19	44	29	4,42	30
422100450235	4,54	25,4	1	152	470	670	228	23	36	76	22	52	34	4,05	30
422100450237	4,54	25,4	1	305	620	970	380	23	36	76	22	52	34	5,08	30
422100450236	4,54	25,4	1	457	680	1.260	532	23	36	76	22	52	34	6,03	30
422100450230	4,54	25,4	1	610	930	1.580	685	23	36	76	22	52	34	7,71	30
422100690230	6,89	31,8	1-1/4	305	690	1.050	384	29	46	90	28	71	44	8,81	30
422100690235	6,89	31,8	1-1/4	457	850	1.350	537	29	46	90	28	71	44	11	30
422100690236	6,89	31,8	1-1/4	610	990	1.650	689	29	46	90	28	71	44	12,9	30
422100970230	9,71	38,1	1-1/2	205	725	1.105	400	32	54	103	35	71	52	13,1	30
422100970235	9,71	38,1	1-1/2	457	880	1.410	553	32	54	103	35	71	52	15,9	30
422100970236	9,71	38,1	1-1/2	610	1.030	1.715	705	32	54	103	35	71	52	17,8	30
422101270230	12,7	44,5	1-3/4	457	950	1.410	568	38	60	117	41	86	66	24,4	30
422101270235	12,7	44,5	1-3/4	610	1.100	1.711	721	38	60	117	41	86	66	27,5	30
422101680230	16,8	51	2	610	1.235	1.845	738	45	68	146	51	94	66	40,4	30
422102720230	27,2	63,5	2-1/2	610	1.315	1.925	789	51	79	165	57	113	76	68	30
422103400230	34	70	2-3/4	610	1.370	1.980	789	57	82	177	70	106	92	83	30

**Blaupause**

