Lifting Solutions Group
Axel Johnson International

STOBITEX Wear Protection Sleeve PU-1/single

Product information

Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as double sided sheathes, STOBITEX Wear Protection Sleeve PU-2/double side.

... *Read more*




Material: Polyurethane.
Temperature range: Approx. -30° up to +70°C, short expose to approx. +90°C.

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

STOBITEX Wear Protection Sleeve PU-1/single

Blueprint



© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

STOBITEX Wear Protection Sleeve PU-1/single

Technical data

Part code	Size	Inside width mm	Height mm	For 2 layer lifting mm	For 4 layer lifting mm	For roundslings ton	Weight kg/m
80255040105	50	40	10	30	-	-	0.85
8025PU15040205	50	40	20	-	30	-	0.9
8025PU17060125	70	60	12	50	-	-	1.25
8025PU17060175	70	60	17	-	50	-	1.3
8025PU18070125	80	70	12	60	-	-	1.3
8025PU18070245	80	70	24	-	60	-	1.35
8025PU18575175	85	75	12	-	-	1	1.35
8025PU19585245	95	85	24	-	-	2	1.5
8025PU1110100125	110	100	12	90	-	-	1.55
8025PU1110100175	110	100	17	-	-	3	1.6
8025PU1110100245	110	100	24	-	90	-	1.6
8025PU1145135125	145	135	12	120	-	-	2
8025PU1145135245	145	135	24	-	120	-	2.1
8025PU1170160125	170	160	12	150	-	-	2.3
8025PU1170160175	170	160	17	-	-	6	2.4
8025PU1170160245	170	160	24	-	150	-	2.4
8025PU1200190125	200	190	12	180	-	-	2.6
8025PU1200190175	200	190	17	-	-	8	2.65
8025PU1200190245	200	190	24	-	180	-	2.7
8025PU1230220365	230	220	36	-	-	10	3.5
8025PU1260250158	260	250	15	240	-	-	3.9
8025PU1290280308	290	280	30	-	-	15	4.4
8025PU1330320158	330	320	15	300	-	-	4.4
8025PU1330320308	330	320	30	-	300	-	4.8
8025PU1330320458	330	320	45	-	-	20	5.3

© November 2026 - All Rights Reserved