



## HSC S Short Stroke Hydraulic Cylinder

### Product information

Holmatro Short stroke cylinders (HSC) - Spring return

#### Unique specifications:

- Compact version, efficient in case of limited insertion space
- Stroke of 50mm on all models

#### Standard supplied with:

- Dirt scraper ring
  - Protects against pollution
  - Increases the life span
- Superior seal for an excellent static and dynamic sealing
- Splined plunger, no saddle needed
- High flow female coupler A118

#### Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

**Material:** Steel

| Part code     | Code       | WLL<br>ton | Stroke<br>mm | Closed height<br>mm | required oil cc | Capacity<br>kN/t | angle A1 ° | Weight<br>kg | Delivery time |
|---------------|------------|------------|--------------|---------------------|-----------------|------------------|------------|--------------|---------------|
| 5211100112300 | HSC 10 S 5 | 10         | 50           | 100                 | 69.3            | 99.8 / 10.2      | 5          | 2.9          | 14            |
| 5211100112301 | HSC 20 S 5 | 20         | 50           | 103                 | 141.4           | 203.6 / 20.8     | 5          | 5.5          | 14            |
| 5211100112302 | HSC 30 S 5 | 30         | 50           | 106                 | 221             | 318.1 / 32.4     | -          | 6.1          | 14            |

## Blueprint

