

Lifting Beam T-A-SL

Product information

The lifting beam of the T-A-SL series has an eye suspension for single hooks according to DIN 15401 on the crane side and shackle bars on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry [... Read more](#)



Material: Construction steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +100°C

Finish: RAL 3000 (flame red)

Standard: EN 13155

Lifting Beam T-A-SL

Blueprint



Lifting Beam T-A-SL

Technical data

Part code	WLL ton	Length m	H mm	L min. mm	L max. mm	S mm	T mm	W mm	Weight kg
6205TASL22000	2	1-2	135	1,000	2,000	50	20	65	56
6205TASL23000	2	1.5-3	135	1,500	3,000	50	20	65	94
6205TASL24000	2	2-4	135	2,000	4,000	50	20	65	148
6205TASL25000	2	2.5-5	135	2,500	5,000	50	20	65	250
6205TASL26000	2	3-6	135	3,000	6,000	50	20	65	295
6205TASL32000	3	1.04-2	150	1,040	2,000	60	25	75	71
6205TASL33000	3	1.56-3	150	1,560	3,000	60	25	75	138
6205TASL34000	3	2.08-4	150	2,080	4,000	60	25	75	210
6205TASL35000	3	2.6-5	150	2,600	5,000	60	25	75	305
6205TASL36000	3	3-6	150	3,000	6,000	60	25	75	429
6205TASL52000	5	1.1-2	170	1,100	2,000	90	25	85	111
6205TASL53000	5	1.56-3	170	1,560	3,000	90	25	85	179
6205TASL54000	5	2.02-4	170	2,020	4,000	90	25	85	265
6205TASL55000	5	2.66-5	170	2,660	5,000	90	25	85	447
6205TASL56000	5	3.12-6	170	3,120	6,000	90	25	85	608
6205TASL82000	8	1-2	210	1,000	2,000	100	30	105	166
6205TASL83000	8	1.6-3	210	1,600	3,000	100	30	105	262
6205TASL84000	8	2-4	210	2,000	4,000	100	30	105	373
6205TASL85000	8	2.6-5	210	2,600	5,000	100	30	105	608
6205TASL86000	8	3-6	210	3,000	6,000	100	30	105	784
6205TASL102000	10	1.08-2	240	1,080	2,000	115	40	120	182
6205TASL103000	10	1.62-3	240	1,620	3,000	115	40	120	314
6205TASL104000	10	2.16-4	240	2,160	4,000	115	40	120	433
6205TASL105000	10	2.7-5	240	2,700	5,000	115	40	120	692
6205TASL106000	10	3.01-6	240	3,010	6,000	115	40	120	910