

Lifting Beam T-A-VR

Product information

The lifting beam of the T-A-VR series has an eye suspension for single hooks according to DIN 15401 on the crane side and adjustable lifting frames on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry [... Read more](#)



Material: Construction steel

Marking: According to standard, CE-marked


Temperature range: -20°C up to +100°C

Finish: RAL 3000 (flame red)

Standard: EN 13155

Lifting Beam T-A-VR

Blueprint



Lifting Beam T-A-VR

Technical data

Part code	WLL ton	Length m	H mm	L min. mm	L max. mm	S mm	T mm	W mm	Weight kg
6205TAVR22000	2	1-2	135	1,000	2,000	50	20	65	53
6205TAVR23000	2	1.5-3	135	1,400	3,000	50	20	65	100
6205TAVR24000	2	2-4	135	2,000	4,000	50	20	65	127
6205TAVR25000	2	2.5-5	135	2,500	5,000	50	20	65	197
6205TAVR26000	2	3-6	135	3,000	6,000	50	20	65	229
6205TAVR32000	3	1-2	150	1,000	2,000	100	25	75	76
6205TAVR33000	3	1.5-3	150	1,500	3,000	100	25	75	131
6205TAVR34000	3	2-4	150	2,000	4,000	100	25	75	165
6205TAVR35000	3	2.5-5	150	2,500	5,000	100	25	75	246
6205TAVR36000	3	3-6	150	3,000	6,000	100	25	75	297
6205TAVR52000	5	1-2	170	1,000	2,000	100	25	85	105
6205TAVR53000	5	1.5-3	170	1,500	3,000	100	25	85	167
6205TAVR54000	5	2-4	170	2,000	4,000	100	25	85	249
6205TAVR55000	5	2.5-5	170	2,500	5,000	100	25	85	363
6205TAVR56000	5	3-6	170	3,000	6,000	100	25	85	426
6205TAVR82000	8	1-2	210	1,000	2,000	100	30	105	151
6205TAVR83000	8	1.5-3	210	1,500	3,000	100	30	105	222
6205TAVR84000	8	2-4	210	2,000	4,000	100	30	105	326
6205TAVR85000	8	2.5-5	210	2,500	5,000	100	30	105	424
6205TAVR86000	8	3-6	210	3,000	6,000	100	30	105	642
6205TAVR102000	10	1-2	240	1,000	2,000	100	40	120	157
6205TAVR103000	10	1.5-3	240	1,500	3,000	100	40	120	252
6205TAVR104000	10	2-4	240	2,000	4,000	100	40	120	349
6205TAVR105000	10	2.5-5	240	2,500	5,000	100	40	120	524
6205TAVR106000	10	3-6	240	3,000	6,000	100	40	120	670