

SR 24V low voltage control electric chain hoist

Product information



Rema® SR is technically advanced electric chain hoist with the most important advantages being the very high duty cycle and modular construction.

Properties

- 400 V, 3 Ph, 50 Hz, 24 V control voltage IP 55, isolation class F.
- Equipped with limit switches for highest and lowest hook position.
- Very low construction height
- Very high duty cycle due to air-cooled motor.
- User-friendly and maintenance-friendly due to modular design.
- Patented braking system that holds the load at any desired height.
- Slip clutch against overload.
- Due to the modular design, the motor, closed drive, brake and drive motor can be replaced independently of each other.
- Simple and quick to build from single-fall to double-fall hoist.
- Load chain Class DAT (Grade 8).

Standard delivery

- 3 m lifting height (max distance between top and bottom hook).
- Control height of 1,8 meter.
- Hoist equipped with thermal overload protection
- *Model 110/111 supplied with one hole suspension plate.
- 1 m power cable.
- Chain container.
- Trolley not included.

Option

[... Read more](#)


Marking: According to standard, CE-marked

Temperature range: Hoist equipped with thermal overload protection

Standard: EN 12100, EN 14492, EN 818-7

SR 24V low voltage control electric chain hoist

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108510003	8717365178931	0.125	3	8	1	SR030/62- 125/1-8- 24V-3	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	16
540108510013	8717365179013	0.125	3	8/2	1	SR031/53- 125/1-8/2- 24V-3	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	16
540108510004	8717365178948	0.125	4	8	1	SR030/62- 125/1-8- 24V-4	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	17
540108510014	8717365179020	0.125	4	8/2	1	SR031/53- 125/1-8/2- 24V-4	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	17
540108510005	8717365178955	0.125	5	8	1	SR030/62- 125/1-8- 24V-5	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	18
540108510015	8717365179037	0.125	5	8/2	1	SR031/53- 125/1-8/2- 24V-5	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	18
540108510006	8717365178962	0.125	6	8	1	SR030/62- 125/1-8- 24V-6	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	19
540108510016	8717365179044	0.125	6	8/2	1	SR031/53- 125/1-8/2- 24V-6	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	19
540108510007	8717365178979	0.125	7	8	1	SR030/62- 125/1-8- 24V-7	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	20

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108510017	8717365179051	0.125	7	8/2	1	SR031/53- 125/1-8/2- 24V-7	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	20
540108510008	8717365178986	0.125	8	8	1	SR030/62- 125/1-8- 24V-8	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	21
540108510018	8717365179068	0.125	8	8/2	1	SR031/53- 125/1-8/2- 24V-8	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	21
540108510009	8717365178993	0.125	9	8	1	SR030/62- 125/1-8- 24V-9	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	22
540108510019	8717365179075	0.125	9	8/2	1	SR031/53- 125/1-8/2- 24V-9	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	22
5401085100010	8717365179006	0.125	10	8	1	SR030/62- 125/1-8- 24V-10	0.55	30	60	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	23
5401085100110	8717365179082	0.125	10	8/2	1	SR031/53- 125/1-8/2- 24V-10	0.32/0.08	30	60/40	4m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	23
540108510033	8717365179099	0.25	3	8/2	1	SR031/51- 250/1-8/2- 24V-3	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	17
540108510063	8717365179174	0.25	3	8	1	SR030/64- 250/1-8- 24V-3	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	17
540108510034	8717365179105	0.25	4	8/2	1	SR031/51- 250/1-8/2- 24V-4	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	18
540108510064	8717365179181	0.25	4	8	1	SR030/64- 250/1-8- 24V-4	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	18
540108510035	8717365179112	0.25	5	8/2	1	SR031/51- 250/1-8/2- 24V-5	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	19
540108510065	8717365179198	0.25	5	8	1	SR030/64- 250/1-8- 24V-5	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	19
540108510036	8717365179129	0.25	6	8/2	1	SR031/51- 250/1-8/2- 24V-6	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	20

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108510066	8717365179204	0.25	6	8	1	SR030/64- 250/1-8- 24V-6	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	20
540108510037	8717365179136	0.25	7	8/2	1	SR031/51- 250/1-8/2- 24V-7	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	21
540108510067	8717365179211	0.25	7	8	1	SR030/64- 250/1-8- 24V-7	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	21
540108510038	8717365179143	0.25	8	8/2	1	SR031/51- 250/1-8/2- 24V-8	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	22
540108510068	8717365179228	0.25	8	8	1	SR030/64- 250/1-8- 24V-8	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	22
540108510039	8717365179150	0.25	9	8/2	1	SR031/51- 250/1-8/2- 24V-9	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	23
540108510069	8717365179235	0.25	9	8	1	SR030/64- 250/1-8- 24V-9	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	23
5401085100310	8717365179167	0.25	10	8/2	1	SR031/51- 250/1-8/2- 24V-10	0.32/0.08	30	50/25	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	24
5401085100610	8717365179242	0.25	10	8	1	SR030/64- 250/1-8- 24V-10	0.55	30	50	3m	500	5.2 x 15	12	212	192	220	437	409	547	516	20	24
540108510093	8717365179259	0.5	3	4/1	2	SR031/51- 500/2-4/1- 24V-3	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	18
540108610133	8717365101595	0.5	3	8	1	SR030/52- 500/1-8- 24V-3	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	18
540108610134	8717365101601	0.5	4	8	1	SR030/52- 500/1-8- 24V-4	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	19
540108510094	8717365179266	0.5	4	4/1	2	SR031/51- 500/2-4/1- 24V-4	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	19.5
540108610135	8717365101618	0.5	5	8	1	SR030/52- 500/1-8- 24V-5	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	20

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108610136	8717365101625	0.5	6	8	1	SR030/52- 500/1-8- 24V-6	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	21
540108510095	8717365179273	0.5	5	4/1	2	SR031/51- 500/2-4/1- 24V-5	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	21
540108610137	8717365101632	0.5	7	8	1	SR030/52- 500/1-8- 24V-7	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	22
540108510096	8717365179280	0.5	6	4/1	2	SR031/51- 500/2-4/1- 24V-6	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	22.5
540108610138	8717365101649	0.5	8	8	1	SR030/52- 500/1-8- 24V-8	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	23
540108510097	8717365179297	0.5	7	4/1	2	SR031/51- 500/2-4/1- 24V-7	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	24
540108610139	8717365101656	0.5	9	8	1	SR030/52- 500/1-8- 24V-9	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	24
5401086101310	8717365101663	0.5	10	8	1	SR030/52- 500/1-8- 24V-10	0.7	25	40	1Bm	2,000	5.2 x 15	8	212	192	220	437	409	547	516	20	25
540108510098	8717365179303	0.5	8	4/1	2	SR031/51- 500/2-4/1- 24V-8	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	25.5
540108510099	8717365179310	0.5	9	4/1	2	SR031/51- 500/2-4/1- 24V-9	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	27
5401085100910	8717365179327	0.5	10	4/1	2	SR031/51- 500/2-4/1- 24V-10	0.32/0.08	15	50/25	3m	500	5.2 x 15	4	212	192	220	485	454	547	516	22	28.5
540108610163	8717365182761	0.5	3	8/2	1	SR071/54- 500/1-8/2- 24V-3	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	45
540108610164	8717365182778	0.5	4	8/2	1	SR071/54- 500/1-8/2- 24V-4	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	46.5
540108610165	8717365182785	0.5	5	8/2	1	SR071/54- 500/1-8/2- 24V-5	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	48

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108610166	8717365182792	0.5	6	8/2	1	SR071/54-500/1-8/2-24V-6	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	49.5
540108610167	8717365182808	0.5	7	8/2	1	SR071/54-500/1-8/2-24V-7	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	51
540108610168	8717365182815	0.5	8	8/2	1	SR071/54-500/1-8/2-24V-8	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	52.5
540108610169	8717365182822	0.5	9	8/2	1	SR071/54-500/1-8/2-24V-9	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	54
5401086101610	8717365182839	0.5	10	8/2	1	SR071/54-500/1-8/2-24V-10	0.9/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	55.5
540108610153	8717365101830	1	3	4	2	SR030/52-1000/2-4-24V-3	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	20
540108610154	8717365101847	1	4	4	2	SR030/52-1000/2-4-24V-4	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	21.5
540108610155	8717365101854	1	5	4	2	SR030/52-1000/2-4-24V-5	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	23
540108610156	8717365101861	1	6	4	2	SR030/52-1000/2-4-24V-6	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	24.5
540108610157	8717365101878	1	7	4	2	SR030/52-1000/2-4-24V-7	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	26
540108610158	8717365101885	1	8	4	2	SR030/52-1000/2-4-24V-8	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	27.5
540108610159	8717365101892	1	9	4	2	SR030/52-1000/2-4-24V-9	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	29
5401086101510	8717365101908	1	10	4	2	SR030/52-1000/2-4-24V-10	0.7	12	40	1Bm	2,000	5.2 x 15	4	212	192	220	485	454	547	516	22	30.5
540108510333	8717365179334	1	3	6	1	SR070/55-1000/1-6-24V-3	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	45

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108510334	8717365179341	1	4	6	1	SR070/55- 1000/1-6- 24V-4	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	46.5
540108510335	8717365179358	1	5	6	1	SR070/55- 1000/1-6- 24V-5	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	48
540108510336	8717365179365	1	6	6	1	SR070/55- 1000/1-6- 24V-6	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	49.5
540108510337	8717365179372	1	7	6	1	SR070/55- 1000/1-6- 24V-7	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	51
540108510338	8717365179389	1	8	6	1	SR070/55- 1000/1-6- 24V-8	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	52.5
540108610293	8717365101991	1	3	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-3	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	53
540108510339	8717365179396	1	9	6	1	SR070/55- 1000/1-6- 24V-9	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	54
5401085103310	8717365179402	1	10	6	1	SR070/55- 1000/1-6- 24V-10	1.1	17	40	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	55.5
540108610294	8717365102004	1	4	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-4	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	55.5
540108610295	8717365102011	1	5	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-5	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	58
540108610296	8717365102028	1	6	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-6	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	60.5
540108610297	8717365102035	1	7	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-7	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	63
540108610298	8717365102042	1	8	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-8	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	65.5
540108610299	8717365102059	1	9	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-9	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	68

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
5401086102910	8717365102066	1	10	6/1,5	1	SR071/55- 1T/1-6/1,5- 24V-10	1.1/0.2	17	60/25	2m	2,000	7.2 x 21	5	266	232	274	500	460	607	567	22	70.5
540108610443	8717365182938	1.6	3	8/2	1	SR091/55- 1,6/1-8/2- 24V-3	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	78
540108610444	8717365182945	1.6	4	8/2	1	SR091/55- 1,6/1-8/2- 24V-4	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	80.3
540108610445	8717365182952	1.6	5	8/2	1	SR091/55- 1,6/1-8/2- 24V-5	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	82.6
540108610446	8717365182969	1.6	6	8/2	1	SR091/55- 1,6/1-8/2- 24V-6	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	84.9
540108610447	8717365182976	1.6	7	8/2	1	SR091/55- 1,6/1-8/2- 24V-7	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	87.2
540108610448	8717365182983	1.6	8	8/2	1	SR091/55- 1,6/1-8/2- 24V-8	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	89.5
540108610449	8717365182990	1.6	9	8/2	1	SR091/55- 1,6/1-8/2- 24V-9	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	91.8
5401086104410	8717365182921	1.6	10	8/2	1	SR091/55- 1,6/1-8/2- 24V-10	3/0.75	18	60/25	2m	3,200	9.0 x 27	10	359	283	359	615	548	746	680	28	94.1
540108610313	8717365102479	2	3	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 3	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	53
540108610353	8717365102554	2	3	5	2	SR070/53- 2T/2-5-24V- 3	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	53
540108610314	8717365102486	2	4	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 4	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	55.5
540108610354	8717365102561	2	4	5	2	SR070/53- 2T/2-5-24V- 4	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	55.5

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108610315	8717365102493	2	5	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 5	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	58
540108610355	8717365102578	2	5	5	2	SR070/53- 2T/2-5-24V- 5	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	58
540108610316	8717365102509	2	6	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 6	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	60.5
540108610356	8717365102585	2	6	5	2	SR070/53- 2T/2-5-24V- 6	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	60.5
540108610317	8717365102516	2	7	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 7	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	63
540108610357	8717365102592	2	7	5	2	SR070/53- 2T/2-5-24V- 7	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	63
540108610318	8717365102523	2	8	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 8	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	65.5
540108610358	8717365102608	2	8	5	2	SR070/53- 2T/2-5-24V- 8	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	65.5
540108610319	8717365102530	2	9	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 9	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	68
540108610359	8717365102615	2	9	5	2	SR070/53- 2T/2-5-24V- 9	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	68
5401086103110	8717365102547	2	10	3/0,75	2	SR071/55- 2T/2- 3/0,75-24V- 10	1.1/0.2	8	60/25	2m	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	70.5
5401086103510	8717365102622	2	10	5	2	SR070/53- 2T/2-5-24V- 10	1.7	8	60	1Am	2,000	7.2 x 21	4	266	232	274	601	561	607	567	28	70.5

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108610533	8717365102714	2.5	3	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-3	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	108
540108610534	8717365102721	2.5	4	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-4	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	111.2
540108610535	8717365102738	2.5	5	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-5	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	114.4
540108610536	8717365102745	2.5	6	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-6	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	117.6
540108610537	8717365102752	2.5	7	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-7	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	120.8
540108610538	8717365102769	2.5	8	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-8	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	124
540108610539	8717365102776	2.5	9	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-9	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	127.2
5401086105310	8717365102783	2.5	10	10/2,5	1	SR111/52- 2,5T/10/2,5- 24V-10	4.4/1.1	12	40/25	2m	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	130.4
540108610463	8717365182853	3.2	3	4/1	2	SR091/55- 3,2/2-4/1- 24V-3	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	88
540108610464	8717365182860	3.2	4	4/1	2	SR091/55- 3,2/2-4/1- 24V-4	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	92
540108610465	8717365182877	3.2	5	4/1	2	SR091/55- 3,2/2-4/1- 24V-5	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	96
540108610466	8717365182884	3.2	6	4/1	2	SR091/55- 3,2/2-4/1- 24V-6	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	100
540108610467	8717365182891	3.2	7	4/1	2	SR091/55- 3,2/2-4/1- 24V-7	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	104
540108610573	8717365103032	3.2	3	8/2	1	SR111/54- 3,2T/1-8/2- 24V-3	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	108

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108610468	8717365182907	3.2	8	4/1	2	SR091/55-3,2T/2-4/1-24V-8	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	108
540108610574	8717365103049	3.2	4	8/2	1	SR111/54-3,2T/1-8/2-24V-4	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	111.2
540108610469	8717365182914	3.2	9	4/1	2	SR091/55-3,2T/2-4/1-24V-9	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	112
540108610575	8717365103056	3.2	5	8/2	1	SR111/54-3,2T/1-8/2-24V-5	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	114.4
5401086104610	8717365182846	3.2	10	4/1	2	SR091/55-3,2T/2-4/1-24V-10	3/0.75	9	60/25	2m	3,200	9.0 x 27	5	359	283	359	615	548	746	680	28	116
540108610576	8717365103063	3.2	6	8/2	1	SR111/54-3,2T/1-8/2-24V-6	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	117.6
540108610577	8717365103070	3.2	7	8/2	1	SR111/54-3,2T/1-8/2-24V-7	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	120.8
540108610578	8717365103087	3.2	8	8/2	1	SR111/54-3,2T/1-8/2-24V-8	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	124
540108610579	8717365103094	3.2	9	8/2	1	SR111/54-3,2T/1-8/2-24V-9	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	127.2
5401086105710	8717365103100	3.2	10	8/2	1	SR111/54-3,2T/1-8/2-24V-10	4.4/1.1	12	25/25	1Bm	6,300	11.3 x 31	6	359	291	410	732	678	792	738	30	130.4
540108610553	8717365103193	5	3	5/1,25	2	SR111/52-5T/2-5/1,25-24V-3	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	125
540108610554	8717365103209	5	4	5/1,25	2	SR111/52-5T/2-5/1,25-24V-4	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	131
540108610555	8717365103216	5	5	5/1,25	2	SR111/52-5T/2-5/1,25-24V-5	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	137

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
540108610556	8717365103223	5	6	5/1,25	2	SR111/52- 5T/2- 5/1,25-24V- 6	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	143
540108610557	8717365103230	5	7	5/1,25	2	SR111/52- 5T/2- 5/1,25-24V- 7	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	149
540108610558	8717365103247	5	8	5/1,25	2	SR111/52- 5T/2- 5/1,25-24V- 8	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	155
540108610559	8717365103254	5	9	5/1,25	2	SR111/52- 5T/2- 5/1,25-24V- 9	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	161
5401086105510	8717365103261	5	10	5/1,25	2	SR111/52- 5T/2- 5/1,25-24V- 10	4.4/1.1	6	40/25	2m	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	167
540108610593	8717365103278	6.3	3	4/1	2	SR111/54- 6,3T/2-4/1- 24V-3	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	125
540108610594	8717365103285	6.3	4	4/1	2	SR111/54- 6,3T/2-4/1- 24V-4	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	131
540108610595	8717365103292	6.3	5	4/1	2	SR111/54- 6,3T/2-4/1- 24V-5	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	137
540108610596	8717365103308	6.3	6	4/1	2	SR111/54- 6,3T/2-4/1- 24V-6	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	143
540108610597	8717365103315	6.3	7	4/1	2	SR111/54- 6,3T/2-4/1- 24V-7	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	149
540108610598	8717365103322	6.3	8	4/1	2	SR111/54- 6,3T/2-4/1- 24V-8	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	155
540108610599	8717365103339	6.3	9	4/1	2	SR111/54- 6,3T/2-4/1- 24V-9	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	161

SR 24V low voltage control electric chain hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Duty group of hoist FEM 9.511	Trolley type kg	Load chain mm	Standard chain bag for lifting height m	A mm	B mm	C mm	G mm	G2 mm	H mm	H2 mm	J mm	Weight kg
5401086105910	8717365103346	6.3	10	4/1	2	SR111/54- 6,3T/2-4/1- 24V-10	4.4/1.0	6	25/25	1Bm	6,300	11.3 x 31	3	359	291	410	861	807	792	738	42	167