



## HFN push trolley

### Product information



REMA HFN trolleys can only be assembled together with the REMA SR electric chain hoists.

#### Properties

- Double axle design.
- Wheel rupture supports and anti-surge devices.
- Equipped with steel machined wheels.
- Assembly and suspension plates not included.

**Marking:** According to standard, CE-marked

**Standard:** EN 12100, EN 13157

**Note:** Always mention the right flange width in mm.

Part code	GTIN No.	WLL ton	Beam width	Model	D mm	F mm	K mm	L	M mm	Weight kg	Delivery time
R0814001-1	8717365149061	0.5	50-106	HFN/500KG D.LOOPKAT 50-106	70	50-106	33	200	112	8	30
R0814001-2	8717365149078	0.5	110-200	HFN/500KG D.LOOPKAT 110-200	70	110-200	33	200	112	8	30
R0814001-3	8717365149092	0.5	210-300	HFN/500KG D.LOOPKAT 210-300	70	210-300	33	200	112	8	30
R0814003-1	8717365149139	2	66-135	HFN/1T/2T D.LOOPKAT 66-135	70	66-135	35	200	112	10	30
R0814003-2	8717365149146	2	137-215	HFN/1T/2T D.LOOPKAT 137-215	70	137-215	35	200	112	10	30
R0814003-3	8717365149153	2	220-300	HFN/1T/2T D.LOOPKAT 220-300	70	220-300	35	200	112	10	30
R0814003-4	8717365179617	2	66-135	HFN/1T/2T/5,2 D.LOOPKAT 66-135	70	66-135	35	200	112	10	30
R0814003-5	8717365179624	2	137-215	HFN/1T/2T/5,2 D.LOOPKAT 137-215	70	137-215	35	200	112	10	30
R0814003-6	8717365179631	2	220-300	HFN/1T/2T/5,2 D.LOOPKAT 220-300	70	220-300	35	200	112	10	30
R0814005-1	8717365149160	3.2	82-155	HFN/3200KG D.LOOPKAT 82-155	103	82-155	35	288.5	152.5	22	30
R0814005-2	8717365149177	3.2	137-215	HFN/3200KG D.LOOPKAT 137-215	103	137-215	35	288.5	152.5	22	30
R0814005-3	8717365149184	3.2	220-300	HFN/3200KG D.LOOPKAT 220-300	103	220-300	35	288.5	152.5	22	30
R0814007-2	8717365149245	6.3	160-226	HFN/6300KG D.LOOPKAT 160-226	122	160-226	36	351	191	47	30
R0814007-3	8717365149252	6.3	240-310	HFN/6300KG D.LOOPKAT 240-310	122	240-310	36	351	191	47	30

# Blueprint

