CERTEX | Lifting Solutions Group
Axel Johnson International

# Select 2 OD lever hoist (with overload device)

**Product information**

REMA®

The Rema Select 2 OD ratchet hoist with serial built-in overload device, except 250 kg *, for safe working during lifting, pulling, tensioning or lashing.

**Properties**

- The innovative overload device ensures safer operation of the hoist.
- Overload device system makes it possible to lower the load in a controlled way.
- Overload device prevents dangerous overloading of the hoist and construction.
- Low leverage at full load due to bearing.
- Equipped with a double pawl system.
- Brake fitted with asbestos free friction discs.
- Load chain wheel is made of precision and wear-resistant alloy steel.
- Freewheel is possible in unloaded condition.
- Top and bottom swivel hook with robust safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain Grade 8.
- Lever with REMA rubber anti-slip handle.
- * = without overload protection.

**Standard delivery**

- 1,5 m lifting height (max distance between top and bottom hook).
- 250 kg without overload device.

**Option**

- Available in other lifting heights.

... *Read more*

**Marking:** According to standard, CE-marked
**Standard:** EN 818-7, EN 13157

**Safety factor:** 3

© October 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Select 2 OD lever hoist (with overload device)

## Blueprint



## Technical data

| Part code | GTIN No. | WLL kg | Lifting height m | Number of falls | Model | Load chain mm | Construction height mm | Hand force max. kg | A mm | B mm | C mm | D mm | E mm | F mm | H mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 5005022000015 | 8717365263910 | 250 | 1.5 | 1 | S2-250KG*-1,5M | 4.0 x 12 | 235 | 28.2 | 100 | 70 | 86 | 163 | 20 | 31 | 235 | 2.5 |
| 500502200003 | 8717365263927 | 250 | 3 | 1 | S2-250KG*-3M | 4.0 x 12 | 235 | 28.2 | 100 | 70 | 86 | 163 | 20 | 31 | 235 | 3.1 |
| 5005022000045 | 8717365263934 | 250 | 4.5 | 1 | S2-250KG*-4,5M | 4.0 x 12 | 235 | 28.2 | 100 | 70 | 86 | 163 | 20 | 31 | 235 | 3.7 |
| 500502200006 | 8717365263941 | 250 | 6 | 1 | S2-250KG*-6M | 4.0 x 12 | 235 | 28.2 | 100 | 70 | 86 | 163 | 20 | 31 | 235 | 4.3 |
| 5005022000115 | 8717365263958 | 500 | 1.5 | 1 | S2OD-500KG-1,5M | 5.0 x 15.0 | 310 | 24.8 | 150 | 90 | 18 | 253 | 22 | 32 | 310 | 5.5 |
| 500502200013 | 8717365263965 | 500 | 3 | 1 | S2OD-500KG-3M | 5.0 x 15.0 | 310 | 24.8 | 150 | 90 | 18 | 253 | 22 | 32 | 310 | 6.4 |
| 5005022000145 | 8717365263972 | 500 | 4.5 | 1 | S2OD-500KG-4,5M | 5.0 x 15.0 | 310 | 24.8 | 150 | 90 | 18 | 253 | 22 | 32 | 310 | 7.3 |
| 500502200016 | 8717365263989 | 500 | 6 | 1 | S2OD-500KG-6M | 5.0 x 15.0 | 310 | 24.8 | 150 | 90 | 18 | 253 | 22 | 32 | 310 | 8.2 |
| 5005022000315 | 8717365263996 | 800 | 1.5 | 1 | S2OD-800KG-1,5M | 5.6 x 17.0 | 340 | 26.5 | 158 | 98 | 132 | 273 | 26 | 36 | 340 | 7.15 |
| 500502200033 | 8717365264009 | 800 | 3 | 1 | S2OD-800KG-3M | 5.6 x 17.0 | 340 | 26.5 | 158 | 98 | 132 | 273 | 26 | 36 | 340 | 8.2 |
| 5005022000345 | 8717365264016 | 800 | 4.5 | 1 | S2OD-800KG-4,5M | 5.6 x 17.0 | 340 | 26.5 | 158 | 98 | 132 | 273 | 26 | 36 | 340 | 9.3 |
| 500502200036 | 8717365264023 | 800 | 6 | 1 | S2OD-800KG-6M | 5.6 x 17.0 | 340 | 26.5 | 158 | 98 | 132 | 273 | 26 | 36 | 340 | 10.2 |
| 5005022000515 | 8717365264030 | 1,600 | 1.5 | 1 | S2OD-1600KG-1,5M | 7.1 x 21.0 | 400 | 29.5 | 185 | 111 | 145 | 378 | 29 | 43 | 400 | 10.2 |
| 500502200053 | 8717365264047 | 1,600 | 3 | 1 | S2OD-1600KG-3M | 7.1 x 21.0 | 400 | 29.5 | 185 | 111 | 145 | 378 | 29 | 43 | 400 | 12 |
| 5005022000545 | 8717365264054 | 1,600 | 4.5 | 1 | S2OD-1600KG-4,5M | 7.1 x 21.0 | 400 | 29.5 | 185 | 111 | 145 | 378 | 29 | 43 | 400 | 13.8 |

© October 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Select 2 OD lever hoist (with overload device)

## Technical data

| Part code | GTIN No. | WLL kg | Lifting height m | Number of falls | Model | Load chain mm | Construction height mm | Hand force max. kg | A mm | B mm | C mm | D mm | E mm | F mm | H mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 500502200056 | 8717365264061 | 1,600 | 6 | 1 | S2OD-1600KG-6M | 7.1 x 21.0 | 400 | 29.5 | 185 | 111 | 145 | 378 | 29 | 43 | 400 | 15.6 |
| 5005022000715 | 8717365264078 | 3,200 | 1.5 | 1 | S2OD-3200KG-1,5M | 10.0 x 28.0 | 520 | 33.5 | 212 | 124 | 198 | 418 | 37 | 50 | 520 | 22 |
| 500502200073 | 8717365264085 | 3,200 | 3 | 1 | S2OD-3200KG-3M | 10.0 x 28.0 | 520 | 33.5 | 212 | 124 | 198 | 418 | 37 | 50 | 520 | 25.5 |
| 5005022000745 | 8717365264092 | 3,200 | 4.5 | 1 | S2OD-3200KG-4,5M | 10.0 x 28.0 | 520 | 33.5 | 212 | 124 | 198 | 418 | 37 | 50 | 520 | 29 |
| 500502200076 | 8717365264108 | 3,200 | 6 | 1 | S2OD-3200KG-6M | 10.0 x 28.0 | 520 | 33.5 | 212 | 124 | 198 | 418 | 37 | 50 | 520 | 32.5 |
| 5005022000915 | 8717365264115 | 6,300 | 1.5 | 2 | S2OD-6300KG-1,5M | 10.0 x 28.0 | 640 | 37 | 212 | 124 | 230 | 418 | 43 | 53 | 640 | 34 |
| 500502200093 | 8717365264122 | 6,300 | 3 | 2 | S2OD-6300KG-3M | 10.0 x 28.0 | 640 | 37 | 212 | 124 | 230 | 418 | 43 | 53 | 640 | 41 |
| 5005022000945 | 8717365264139 | 6,300 | 4.5 | 2 | S2OD-6300KG-4,5M | 10.0 x 28.0 | 640 | 37 | 212 | 124 | 230 | 418 | 43 | 53 | 640 | 48 |
| 500502200096 | 8717365264146 | 6,300 | 6 | 2 | S2OD-6300KG-6M | 10.0 x 28.0 | 640 | 37 | 212 | 124 | 230 | 418 | 43 | 53 | 640 | 55 |
| 5005022001115 | 8717365264153 | 9,000 | 1.5 | 3 | S2OD-9000KG-1,5M | 10.0 x 28.0 | 730 | 42 | 212 | 124 | 338 | 418 | 44 | 67 | 730 | 45 |
| 500502200113 | 8717365264160 | 9,000 | 3 | 3 | S2OD-9000KG-3M | 10.0 x 28.0 | 730 | 42 | 212 | 124 | 338 | 418 | 44 | 67 | 730 | 56 |
| 5005022001145 | 8717365264177 | 9,000 | 4.5 | 3 | S2OD-9000KG-4,5M | 10.0 x 28.0 | 730 | 42 | 212 | 124 | 338 | 418 | 44 | 67 | 730 | 67 |
| 500502200116 | 8717365264184 | 9,000 | 6 | 3 | S2OD-9000KG-6M | 10.0 x 28.0 | 730 | 42 | 212 | 124 | 338 | 418 | 44 | 67 | 730 | 78 |

© October 2026 - All Rights Reserved