

Select 2 OD lever hoist (with overload device)

Product information



REMA[®]

The Rema[®] Select 2 OD ratchet hoist with serial built-in overload device, except 250 kg *, for safe working during lifting, pulling, tensioning or lashing.

Properties

- The innovative overload device ensures safer operation of the hoist.
- Overload device system makes it possible to lower the load in a controlled way.
- Overload device prevents dangerous overloading of the hoist and construction.
- Low leverage at full load due to bearing.
- Equipped with a double pawl system.
- Brake fitted with asbestos free friction discs.
- Load chain wheel is made of precision and wear-resistant alloy steel.
- Freewheel is possible in unloaded condition.
- Top and bottom swivel hook with robust safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain Grade 8.
- Lever with REMA rubber anti-slip handle.
- * = without overload protection.

Standard delivery

- 1,5 m lifting height (max distance between top and bottom hook).
- 250 kg without overload device.

Option

- Available in other lifting heights.


... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 818-7, EN 13157

Safety factor: 3

Select 2 OD lever hoist (with overload device)

Blueprint



Technical data

Part code	GTIN No.	WLL kg	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
5005022000015	8717365263910	250	1.5	1	S2-250KG*-1,5M	4.0 x 12	235	28.2	100	70	86	163	20	31	235	2.5
5005022000003	8717365263927	250	3	1	S2-250KG*-3M	4.0 x 12	235	28.2	100	70	86	163	20	31	235	3.1
5005022000045	8717365263934	250	4.5	1	S2-250KG*-4,5M	4.0 x 12	235	28.2	100	70	86	163	20	31	235	3.7
5005022000006	8717365263941	250	6	1	S2-250KG*-6M	4.0 x 12	235	28.2	100	70	86	163	20	31	235	4.3
5005022000115	8717365263958	500	1.5	1	S2OD-500KG-1,5M	5.0 x 15.0	310	24.8	150	90	18	253	22	32	310	5.5
500502200013	8717365263965	500	3	1	S2OD-500KG-3M	5.0 x 15.0	310	24.8	150	90	18	253	22	32	310	6.4
5005022000145	8717365263972	500	4.5	1	S2OD-500KG-4,5M	5.0 x 15.0	310	24.8	150	90	18	253	22	32	310	7.3
500502200016	8717365263989	500	6	1	S2OD-500KG-6M	5.0 x 15.0	310	24.8	150	90	18	253	22	32	310	8.2
5005022000315	8717365263996	800	1.5	1	S2OD-800KG-1,5M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	7.15
500502200033	8717365264009	800	3	1	S2OD-800KG-3M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	8.2
5005022000345	8717365264016	800	4.5	1	S2OD-800KG-4,5M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	9.3
500502200036	8717365264023	800	6	1	S2OD-800KG-6M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	10.2
5005022000515	8717365264030	1,600	1.5	1	S2OD-1600KG-1,5M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	10.2
500502200053	8717365264047	1,600	3	1	S2OD-1600KG-3M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	12
5005022000545	8717365264054	1,600	4.5	1	S2OD-1600KG-4,5M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	13.8

Select 2 OD lever hoist (with overload device)

Technical data

Part code	GTIN No.	WLL kg	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
500502200056	8717365264061	1,600	6	1	S2OD-1600KG-6M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	15.6
5005022000715	8717365264078	3,200	1.5	1	S2OD-3200KG-1,5M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	22
500502200073	8717365264085	3,200	3	1	S2OD-3200KG-3M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	25.5
5005022000745	8717365264092	3,200	4.5	1	S2OD-3200KG-4,5M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	29
500502200076	8717365264108	3,200	6	1	S2OD-3200KG-6M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	32.5
5005022000915	8717365264115	6,300	1.5	2	S2OD-6300KG-1,5M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	34
500502200093	8717365264122	6,300	3	2	S2OD-6300KG-3M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	41
5005022000945	8717365264139	6,300	4.5	2	S2OD-6300KG-4,5M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	48
500502200096	8717365264146	6,300	6	2	S2OD-6300KG-6M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	55
5005022001115	8717365264153	9,000	1.5	3	S2OD-9000KG-1,5M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	45
500502200113	8717365264160	9,000	3	3	S2OD-9000KG-3M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	56
5005022001145	8717365264177	9,000	4.5	3	S2OD-9000KG-4,5M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	67
500502200116	8717365264184	9,000	6	3	S2OD-9000KG-6M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	78