

X-Line lever hoist

Product information



REMA[®]

The Rema[®] X-Line lever hoist for safe and reliable operation during hoisting, pulling, tensioning or lashing.

Properties

- Low effort at full load.
- Increased operational safety due to double pawl system.
- Brake with asbestos free friction discs.
- Freewheel in unloaded condition.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).

Standard delivery

- 1,5 m lifting height (max distance between top and bottom hook).

Option

- Available in other lifting heights.


TUV icon

[... Read more](#)

Marking: According to standard, CE-marked
Standard: EN 818-7, EN 13157

X-Line lever hoist

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
50050270000	8717365112515	0.25	-	-	X-LH025/250KG	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	2.5
5005027000015	8717365112522	0.25	1.5	1	X-LH/250KG/1,5M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	2.5
500502700003	8717365112485	0.25	3	1	X-LH/250KG/3M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	3.1
5005027000045	8717365112492	0.25	4.5	1	X-LH/250KG/4,5M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	3.7
500502700006	8717365112508	0.25	6	1	X-LH/250KG/6M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	4.3
50050270001	8717365088575	0.5	-	-	X-LH050/500KG	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	5.5
5005027000115	8717365096358	0.5	1.5	1	X-LH/500KG/1,5M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	5.5
500502700013	8717365096860	0.5	3	1	X-LH/500KG/3M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	6.4
5005027000145	8717365096877	0.5	4.5	1	X-LH/500KG/4,5M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	7.3
500502700016	8717365096884	0.5	6	1	X-LH/500KG/6M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	8.2
50050270003	8717365088582	0.8	-	1	X-LH080/800KG	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	7.15
5005027000315	8717365096365	0.8	1.5	1	X-LH/800KG/1,5M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	7.15
500502700033	8717365096891	0.8	3	1	X-LH/800KG/3M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	8.2
5005027000345	8717365096907	0.8	4.5	1	X-LH/800KG/4,5M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	9.3

X-Line lever hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
500502700036	8717365096914	0.8	6	1	X-LH/800KG/6M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	10.4
50050270005	8717365088599	1.6	-	-	X-LH16/1600KG	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	10.2
5005027000515	8717365096372	1.6	1.5	1	X-LH/1600KG/1,5M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	10.2
500502700053	8717365096921	1.6	3	1	X-LH/1600KG/3M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	12
5005027000545	8717365096938	1.6	4.5	1	X-LH/1600KG/4,5M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	13.8
500502700056	8717365096945	1.6	6	1	X-LH/1600KG/6M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	15.6
50050270007	8717365088605	3.2	-	-	X-LH32/3200KG	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	22
5005027000715	8717365096389	3.2	1.5	1	X-LH/3200KG/1,5M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	22
500502700073	8717365096952	3.2	3	1	X-LH/3200KG/3M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	25.5
5005027000745	8717365096969	3.2	4.5	1	X-LH/3200KG/4,5M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	29
500502700076	8717365096976	3.2	6	1	X-LH/3200KG/6M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	32.5
50050270009	8717365088612	6.3	-	-	X-LH63/6300KG	10.0 x 28.0	640	37	212	124	230	418	43	53	640	34
5005027000915	8717365096396	6.3	1.5	2	X-LH/6300KG/1,5M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	34
500502700093	8717365096983	6.3	3	2	X-LH/6300KG/3M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	41
5005027000945	8717365096990	6.3	4.5	2	X-LH/6300KG/4,5M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	48
500502700096	8717365097003	6.3	6	2	X-LH/6300KG/6M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	55
50050270011	8717365088629	9	-	-	X-LH90/9000KG	10.0 x 28.0	730	42	212	124	338	418	44	67	730	45
5005027001115	8717365096402	9	1.5	3	X-LH/9000KG/1,5M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	45
500502700113	8717365097010	9	3	3	X-LH/9000KG/3M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	56
5005027001145	8717365097027	9	4.5	3	X-LH/9000KG/4,5M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	67

X-Line lever hoist

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
500502700116	8717365097034	9	6	3	X-LH/9000KG/6M	10.0 x 28.0	730	42	212	124	338	418	44	67	730	78