

S20P Low headroom Hoist/Push trolley combination

Product information



REMA[®]

These low headroom hoist-trolley combinations are only supplied with Rema[®] Select 200OD hand chain hoist.

Properties

- Low headroom.
- Push trolley.
- Technical detail hand chain hoist, see Select 200OD.
- Wheel fracture support devices for additional safety.
- Adjustable to allow attachment to different beam sizes..

Standard delivery

- Included trolley.
- 3 meters lifting height (max. between top and bottom hook).
- 2.5 m operating height.

Option

- Available in other lifting and operating height on request.


... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

S20P Low headroom Hoist/Push trolley combination

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Beam width	Model	Wheels diameter mm	Load chain mm	Hand chain mm	Minimum radius mm	A mm	B mm	Cmin(mm) mm	F mm	Hmin mm	M mm	S mm	Z mm	Weight kg
502509300013	8717365117183	0.5	3	1	50-203	S20P/200OD/0.5T/3M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	18
502509300014	8717365117190	0.5	4	1	50-203	S20P/200OD/0.5T/4M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	20
502509300015	8717365117206	0.5	5	1	50-203	S20P/200OD/0.5T/5M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	21.5
502509300016	8717365117213	0.5	6	1	50-203	S20P/200OD/0.5T/6M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	23
502509300017	8717365117220	0.5	7	1	50-203	S20P/200OD/0.5T/7M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	25
502509300018	8717365117237	0.5	8	1	50-203	S20P/200OD/0.5T/8M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	26
502509300019	8717365117244	0.5	9	1	50-203	S20P/200OD/0.5T/9M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	28
5025093000110	8717365117251	0.5	10	1	50-203	S20P/200OD/0.5T/10M	55	5.0 x 15	5.0 x 23.7	800	265	258	310.5	1.5-3	243.5	50-203	30	9	30
502509300033	8717365117268	1	3	1	64-305	S20P/200OD/1T/3M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	28
502509300034	8717365117275	1	4	1	64-305	S20P/200OD/1T/4M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	30
502509300035	8717365117282	1	5	1	64-305	S20P/200OD/1T/5M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	32
502509300036	8717365117299	1	6	1	64-305	S20P/200OD/1T/6M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	34
502509300037	8717365117305	1	7	1	64-305	S20P/200OD/1T/7M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	36
502509300038	8717365117312	1	8	1	64-305	S20P/200OD/1T/8M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	38

S20P Low headroom Hoist/Push trolley combination

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Beam width	Model	Wheels diameter mm	Load chain mm	Hand chain mm	Minimum radius mm	A mm	B mm	Cmin(mm) mm	F mm	Hmin mm	M mm	S mm	Z mm	Weight kg
502509300039	8717365117329	1	9	1	64-305	S20P/200OD/1T/9M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	40
5025093000310	8717365117336	1	10	1	64-305	S20P/200OD/1T/10M	68	6.3 x 19.1	5.0 x 23.7	900	385	292	420	1.5-3	340	64-305	37	8	41
502509300053	8717365117343	1.5	3	1	88-305	S20P/200OD/1.5T/3M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	40
502509300054	8717365117350	1.5	4	1	88-305	S20P/200OD/1.5T/4M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	42
502509300055	8717365117367	1.5	5	1	88-305	S20P/200OD/1.5T/5M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	44
502509300056	8717365117374	1.5	6	1	88-305	S20P/200OD/1.5T/6M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	46
502509300057	8717365117381	1.5	7	1	88-305	S20P/200OD/1.5T/7M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	48
502509300058	8717365117398	1.5	8	1	88-305	S20P/200OD/1.5T/8M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	50
502509300059	8717365117404	1.5	9	1	88-305	S20P/200OD/1.5T/9M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	52
5025093000510	8717365117411	1.5	10	1	88-305	S20P/200OD/1.5T/10M	80	7.1 x 21	5.0 x 23.7	1,000	396	360	460	1.5-3	380	88-305	39	10	55.5
502509300073	8717365117428	2	3	1	88-305	S20P/200OD/2T/3M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	44.5
502509300074	8717365117435	2	4	1	88-305	S20P/200OD/2T/4M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	47
502509300075	8717365117442	2	5	1	88-305	S20P/200OD/2T/5M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	49
502509300076	8717365117459	2	6	1	88-305	S20P/200OD/2T/6M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	52
502509300077	8717365117466	2	7	1	88-305	S20P/200OD/2T/7M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	54
502509300078	8717365117473	2	8	1	88-305	S20P/200OD/2T/8M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	56.5
502509300079	8717365117480	2	9	1	88-305	S20P/200OD/2T/9M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	59
5025093000710	8717365117497	2	10	1	88-305	S20P/200OD/2T/10M	80	8.0 x 24	5.0 x 23.7	1,000	396	360	500	1.5-3	405	88-305	38	10	61
502509300093	8717365117503	3	3	2	100-305	S20P/200OD/3T/3M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	66
502509300094	8717365117510	3	4	2	100-305	S20P/200OD/3T/4M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	70

S20P Low headroom Hoist/Push trolley combination

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Beam width	Model	Wheels diameter mm	Load chain mm	Hand chain mm	Minimum radius mm	A mm	B mm	Cmin(mm) mm	F mm	Hmin mm	M mm	S mm	Z mm	Weight kg
502509300095	8717365117527	3	5	2	100-305	S20P/200OD/3T/5M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	73
502509300096	8717365117534	3	6	2	100-305	S20P/200OD/3T/6M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	76.5
502509300097	8717365117541	3	7	2	100-305	S20P/200OD/3T/7M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	80
502509300098	8717365117558	3	8	2	100-305	S20P/200OD/3T/8M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	83
502509300099	8717365117565	3	9	2	100-305	S20P/200OD/3T/9M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	86.5
5025093000910	8717365117572	3	10	2	100-305	S20P/200OD/3T/10M	100	7.1 x 21	5.0 x 23.7	1,200	407	430	590	1.5-3	475	100-305	42	12	90
502509300113	8717365117589	5	3	2	114-305	S20P/200OD/5T/3M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	108
502509300114	8717365117596	5	4	2	114-305	S20P/200OD/5T/4M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	112.5
502509300115	8717365117602	5	5	2	114-305	S20P/200OD/5T/5M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	117
502509300116	8717365117619	5	6	2	114-305	S20P/200OD/5T/6M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	121.5
502509300117	8717365117626	5	7	2	114-305	S20P/200OD/5T/7M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	126
502509300118	8717365117633	5	8	2	114-305	S20P/200OD/5T/8M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	130.5
502509300119	8717365117640	5	9	2	114-305	S20P/200OD/5T/9M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	135
5025093001110	8717365117657	5	10	2	114-305	S20P/200OD/5T/10M	110	9.0 x 27	5.0 x 23.7	1,300	420	420	725	1.5-3	610	114-305	41.5	16	140