CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® Select 200

Product information



The Rema® Select 200 OD is equipped with an overload protection from 500 kg. It is a robust manual chain hoist for heavy and intensive use where safety, ergonomics and a low operating effort are paramount.

Properties

- The new innovative overload protection ensures an improved safer operation of the hoist.
- Overload device system makes it possible to lower the load in a controlled way.
- Equipped with a double pawl system.
- Brake is provided with astbestos free friction discs.
- Top and bottom hooks are equipped with a robust latches.
- Load hooks gradually bend and do not break off suddenly.
- Galvanized load chain Grade 8.
- Galvanized hand chain.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.
- Overload protection from 500 kg up to 10.000 kg.

Option

- Available in any other hoisting and operational heights.
- Chain bucker available up to 10 meter lifting height from 500 kg till 2000 kg.
- Short height in combination with REMA 211/212 trolley bij intermediate link, which replace the top hook.

Warning

... *Read more*


Marking: According to standard, CE-mark
Standard: EN 13157, EN 818-7

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® Select 200

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
500101200003	8717365263637	0.25	3	1	S200-250KG*-3M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	6
500101200004	8717365263644	0.25	4	1	S200/250KG/4M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	7.4
500101200005	8717365263651	0.25	5	1	S200/250KG/5M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	8.8
500101200006	8717365263668	0.25	6	1	S200-250KG*-6M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	10.2
500101200007	8717365092572	0.25	7	1	S200/250KG/7M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	11.6
500101200008	8717365092589	0.25	8	1	S200/250KG/8M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	13
500101200009	8717365092596	0.25	9	1	S200/250KG/9M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	14.4
5001012000010	8717365092602	0.25	10	1	S200/250KG/10M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	15.8
500101200013	8717365263675	0.5	3	1	S200OD-500KG-3M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	10
500101200014	8717365263682	0.5	4	1	S200OD/500KG/4M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	11.6
500101200015	8717365263699	0.5	5	1	S200OD/500KG/5M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	13.2
500101200016	8717365263705	0.5	6	1	S200OD-500KG-6M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	14.8
500101200017	8717365092619	0.5	7	1	S200OD/500KG/7M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	16.4
500101200018	8717365092626	0.5	8	1	S200OD/500KG/8M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	18

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® Select 200

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
500101200019	8717365092633	0.5	9	1	S200OD/500KG/9M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	19.6
5001012000110	8717365092640	0.5	10	1	S200OD/500KG/10M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	21.2
500101200033	8717365263712	1	3	1	S200OD-1000KG-3M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	12
500101200034	8717365263729	1	4	1	S200OD/1000KG/4M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	13.9
500101200035	8717365263736	1	5	1	S200OD/1000KG/5M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	15.8
500101200036	8717365263743	1	6	1	S200OD-1000KG-6M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	17.7
500101200037	8717365092657	1	7	1	S200OD/1000KG/7M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	19.6
500101200038	8717365092664	1	8	1	S200OD/1000KG/8M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	21.5
500101200039	8717365092671	1	9	1	S200OD/1000KG/9M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	23.4
5001012000310	8717365092688	1	10	1	S200OD/1000KG/10M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	25.3
500101200053	8717365263750	1.5	3	1	S200OD-1500KG-3M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	16
500101200054	8717365263767	1.5	4	1	S200OD/1500KG/4M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	18.2
500101200055	8717365263774	1.5	5	1	S200OD/1500KG/5M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	20.4
500101200056	8717365263781	1.5	6	1	S200OD-1500KG-6M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	22.6
500101200057	8717365092695	1.5	7	1	S200OD/1500KG/7M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	24.8
500101200058	8717365092701	1.5	8	1	S200OD/1500KG/8M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	27
500101200059	8717365092718	1.5	9	1	S200OD/1500KG/9M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	29.2
5001012000510	8717365092725	1.5	10	1	S200OD/1500KG/10M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	31.4
500101200073	8717365263798	2	3	1	S200OD-2000KG-3M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	20
500101200074	8717365263804	2	4	1	S200OD/2000KG/4M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	22.4

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® Select 200

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
500101200075	8717365263811	2	5	1	S200OD/2000KG/5M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	24.8
500101200076	8717365263828	2	6	1	S200OD-2000KG-6M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	27.2
500101200077	8717365092732	2	7	1	S200OD/2000KG/7M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	29.6
500101200078	8717365092749	2	8	1	S200OD/2000KG/8M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	32
500101200079	8717365092756	2	9	1	S200OD/2000KG/9M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	34.4
5001012000710	8717365092763	2	10	1	S200OD/2000KG/10M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	36.8
500101200093	8717365263835	3	3	2	S200OD-3000KG-3M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	26
500101200094	8717365263842	3	4	2	S200OD/3000KG/4M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	29.4
500101200095	8717365263859	3	5	2	S200OD/3000KG/5M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	32.8
500101200096	8717365263866	3	6	2	S200OD-3000KG-6M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	36.2
500101200097	8717365092770	3	7	2	S200OD/3000KG/7M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	39.6
500101200098	8717365092787	3	8	2	S200OD/3000KG/8M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	43
500101200099	8717365092794	3	9	2	S200OD/3000KG/9M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	46.4
5001012000910	8717365092800	3	10	2	S200OD/3000KG/10M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	49.8
500101200113	8717365263873	5	3	2	S200OD-5000KG-3M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	41.5
500101200114	8717365263880	5	4	2	S200OD/5000KG/4M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	46
500101200115	8717365263897	5	5	2	S200OD/5000KG/5M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	50.5
500101200116	8717365263903	5	6	2	S200OD-5000KG-6M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	55
500101200117	8717365092817	5	7	2	S200OD/5000KG/7M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	59.5
500101200118	8717365092824	5	8	2	S200OD/5000KG/8M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	64

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® Select 200

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
500101200119	8717365092831	5	9	2	S200OD/5000KG/9M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	68.5
5001012001110	8717365092848	5	10	2	S200OD/5000KG/10M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	73
500101200133	8717365174582	7.5	3	3	S200OD-7500KG-3M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	50
500101200134	8717365174599	7.5	4	3	S200OD/7500KG/4M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	57
500101200135	8717365174605	7.5	5	3	S200OD/7500KG/5M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	64
500101200136	8717365174612	7.5	6	3	S200OD-7500KG-6M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	71
500101200137	8717365174629	7.5	7	3	S200OD/7500KG/7M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	77
500101200138	8717365174636	7.5	8	3	S200OD/7500KG/8M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	84
500101200139	8717365174643	7.5	9	3	S200OD/7500KG/9M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	91
5001012001310	8717365174650	7.5	10	3	S200OD/7500KG/10M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	98
500101200153	8717365174667	10	3	4	S200OD-10000KG-3M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	75
500101200154	8717365174674	10	4	4	S200OD/10.000KG/4M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	83
500101200155	8717365174681	10	5	4	S200OD/10.000KG/5M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	91
500101200156	8717365174698	10	6	4	S200OD-10000KG-6M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	99
500101200157	8717365174704	10	7	4	S200OD/10.000KG/7M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	107
500101200158	8717365174711	10	8	4	S200OD/10.000KG/8M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	115
500101200159	8717365174728	10	9	4	S200OD/10.000KG/9M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	123
5001012001510	8717365174735	10	10	4	S200OD/10.000KG/10M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	131

© November 2026 - All Rights Reserved