

## Dynamometer 04 TX/RX

### Product information



#### Mechanical properties

- Anodized aluminum housing.
- Protection class IP 65.
- Overload indication at 10% inconvenience.
- Test load 2 x WLL.
- Safety factor 5 x WLL.

#### Electrical specifications

- Rechargeable batteries including charger.
- Charger: Input 230 VAC, output 20 VDC.
- Battery operating time about 100 hours.

#### Electronic specifications

- LCD display with 5 positions, digit height 17 mm.
- Operating temperature range between -10 ° C and + 55 ° C
- Accuracy up to approx. 0.15% of the reading value.

#### RX-PORT electrical specifications

- Alkaline batteries (3 x AA type).
- Stand time approx. 150 hours.
- Battery indicator.

#### RX-PORT electronic specifications

- LCD display with 5 positions, 12 mm digit height.
- 433.92 MHz frequency control.
- Operating temperature range -5 ° C to + 55 ° C.

... [Read more](#)

**Marking:** According to standard, CE-marked


**Standard:** EN 13889, EN 13155, EN 12100

**Note:** Includes plastic case, manual and calibration report.

**Safety factor:** 5

## Dynamometer 04 TX/RX

### Blueprint



### Technical data

| Part code | GTIN No.      | WLL ton | Model         | Shackle  | Resolution kg | A mm | B mm | C mm | D mm | E mm | F mm | G mm | Weight kg |
|-----------|---------------|---------|---------------|----------|---------------|------|------|------|------|------|------|------|-----------|
| R1512003  | 8717365025846 | 5       | DSD04-05TX/RX | 6.5t in. | 2             | 232  | 85   | 54   | 27   | 32   | 168  | 32   | 1.85      |
| R1512005  | 8717365021763 | 10      | DSD04-10TX/RX | 12t ex.  | 5             | 315  | 100  | 59   | 39   | 49   | 203  | 56   | 3.6       |
| R1512009  | 8717365021770 | 25      | DSD04-25TX/RX | 25t ex.  | 10            | 350  | 126  | 70   | 55   | 70   | 210  | 70   | 7         |
| R1512011  | 8717365111013 | 50      | DSD04-50TX/RX | 55t ex.  | 20            | 450  | 165  | 98   | 77   | 98   | 260  | 95   | 17        |