CERTEX | Lifting Solutions Group
Axel Johnson International

Dynamometer 05

Product information



REMA®

Mechanical properties

- Aluminum housing.
- Alloy steel pulling unit.
- Test load 2 x WLL (without losing accuracy).
- Safety factor 5 x WLL.
- International Protection Rating / Ingress Protection: IP65 (EN60529).

Electrical specifications

- Alkaline battery (3 x AA type).
- Battery operating time about 180 hours.

Electronic specifications

- Operating temperature range between -5° C to + 55° C.
- Accuracy up to approx. 0.1% of the reading value.
- Battery indicator.

Option

- U-13 Unilock bow schackle (2635013).

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 12100, EN 13155, EN 13889
Note: Includes plastic case, manual and calibration report.


Safety factor: 5

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Dynamometer 05

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Model	Shackle size	Resolution kg	A mm	B mm	C mm	D mm	E mm	F mm	Weight kg
60971514001	8717365111983	0.6	DSD05-0.6T	U-13 ex.	0.2	170	16	21	-	-	-	2.3
60971514003	8717365111990	1	DSD05-1.0T	U-13 ex.	0.5	170	16	21	-	-	-	2.3

© November 2026 - All Rights Reserved